

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED

Budget Bureau No. 1004-0135
Expires March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

DEVON ENERGY CORPORATION (NEVADA)

3. Address and Telephone No.

20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405) 235-3611

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

75' FNL & 1370' FEL, Sec. 9-17S-31E

5. Lease Designation and Serial No.

LC-029426-B

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

H. E. West "B" #54

9. API Well No.

30-015-27150

10. Field and Pool, or Exploratory Area

Grayburg Jackson

11. County or Parish, State

Eddy County, NM

CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Perf'd & acidized

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The following work was performed on this well:

5/14/98 - Ran bit & scraper to 4280'.

5/15/98 - Acidized perfs 4031'-4250' w/2000 gals 15% HCl acid + 4000# rock salt.

Acidized perfs 3766'-3871' w/1500 gals 15% HCl acid + 2500# rock salt.

5/18/98 - Perf'd Lovington 3586'-3671' w/15 - .47" holes. Acidized perfs 3586'-3671' w/1500 gals 15% HCl acid + 30 ball sealers.

5/19/98 - Re-perf'd Lovington 3583'-3635' w/15 holes. Acidized perfs 3583'-3671' w/1500 gals 15% HCl acid + 2000# rock salt.

5/20/98 - Frac'd Lovington perfs 3583'-3671' w/21,000 gals Spectra Frac 3000 G + 35,000# 20/40 Brady sand + 12,300# 20/40 Super LC sand.

5/23/98 - Acidized Grayburg perfs 3230'-3520' w/2800 gals 15% HCl acid + 3000# rock salt.

5/27/98 - Hung well back on production.

14. I hereby certify that the foregoing is true and correct

Signed Karen Byers

Title Engineering Technician

Date 6/1/98

(This space for Federal or State office use)

Approved by _____

Title (ORIG. SGD) DAVID R. GLASS

Date _____

Conditions of approval, if any:

