Submit 3 Copies to Appropriate District Office

State of New Mexico

Form C-103	
Revised 1-1-	89

Energy, Minerals and Natural Resources Department

District Office	TO THE TOTAL AND AND THE TOTAL OF THE TOTAL
DISTRICT I	OIL CONSERVATION DIVISION
P.O. Box 1980, Hobbs, NM 88240	P.O. Box 2088
DISTRICT II	Santa Fe, New Mexico 87504-2088

WELL API NO.	
30-015-27257	
5. Indicate Type of Lease STATE X	FEE
6. State Oil & Gas Lease No.	•

OIL CONSERVATION DIVISION	WELL API NO.		
P.O. Box 1980, Hobbs, NM 88240 P.O. Box 2088	30-015-27257		
DISTRICT II Santa Fe, New Mexico 87504-2088 P.O. Drawer DD, Artesia, NM 88210	5. Indicate Type of Lease STATE X FEE		
DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410	6. State Oil & Gas Lease No. B-9563		
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	7. Lease Name or Unit Agreement Name		
1. Type of Well:	G-J West Coop Unit		
2. Name of Operator	8. Well No. #104		
Mack Energy Corporation 3. Address of Operator 3. Address of Operator 3. Address of Operator 3. Address of Operator	9. Pool name or Wildcat Grayburg Jackson SR QN GB SA		
P.O. Box 1359, Artesia, NM 88211-1359 4. Well Location Unit Letter M : 560 Feet From The South Line and 48	O Feet From The West Line		
Section 21 Township 17S Range 29E 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3598.7 GR	NMPM Eddy County		
Check Appropriate Box to Indicate Nature of Notice, R	Report, or Other Data		
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:		
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING		
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLIN	G OPNS. PLUG AND ABANDONMENT		
CASING TEST AND C	CASING TEST AND CEMENT JOB		
OTHER: Inter	OTHER: Intermediate csg XX		
OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, incl work) SEE RULE 1103.			

Drilled 12 1/4" hole to 815', ran 18 jts. 8 5/8" 24# csg to 791', cement with 150 sx thickset 10# Gilsonite 1/2# Flocele, 3% CC & 550 sx Class C cement 1/4# Flocele, 2% CC. Circ 100sx to pit, plug down @ 5:00 a.m. 1/25/93. Cement fell back, redi mix with 3 yards to surface.

I hereby certify that the information above is true and complete to the best of n	ny knowledge and belief. TILE Production Clerk	DATE 1/26/93 TELEPHIONE NO.
TYPE OR PRINT NAME		
(This space for State Use) ORIGINAL SIGNED BY MIKE WILLIAMS	TITLE	JAN 2 9 1993
APPROVED BY SUPERVISOR, DISTRICT I'CONDITIONS OF APPROVAL, IF ANY:		