

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

*dst*

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

APR - 9 1993  
O. C. D.

WELL API NO.  
30-015-27259

5. Indicate Type of Lease  
STATE  FEE

6. State Oil & Gas Lease No.  
B-1266

7. Lease Name or Unit Agreement Name  
G-J West Coop Unit

8. Well No.  
#106

9. Pool name or Wildcat  
Grayburg Jackson SR QN GB SA

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
OIL WELL  GAS WELL  OTHER

2. Name of Operator  
Mack Energy Corporation

3. Address of Operator  
P.O. Box 1359, Artesia, NM 88211-1359

4. Well Location  
Unit Letter K : 2310 Feet From The South Line and 1480 Feet From The West Line  
Section 21 Township 17S Range 29E NMPM Eddy County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)  
3608.6 GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <u>TD, cmt csg</u> <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 5050' 3/13/93. Ran 123 jts 5 1/2" 17# J-55 LT&C R-3 csg to 5007' with float shoe, float collar & D.V. Tool @ 3600'. First stage cemented w/400sx Class C, 4/10 of 1% Halad-322, 2.5# salt per sack. Circ. 190sx cement off top of D.V. Tool. Second stage cemented w/1100sx Class C, 4/10 of 1% Halad-322, 2.5# salt per sack. Circ. 10sx cement. Plug down @ 6:52 pm 3/13/93. WOC 18 hrs., tstd csg to 1800# f/30 minutes--held okay.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.  
SIGNATURE Crissa D. Carter TITLE Production Clerk DATE 3/17/93  
TYPE OR PRINT NAME Crissa D. Carter TELEPHONE NO. 748-1288

(This space for State Use) ORIGINAL SIGNED BY  
MIKE WILLIAMS  
APPROVED BY SUPERVISOR, DISTRICT II TITLE \_\_\_\_\_ DATE MAR 23 1993  
CONDITIONS OF APPROVAL, IF ANY: