Form 3160-5 (June 1990)

UN ED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

NM OIL NS COMMISSION Drawer DD

Artesia, NM 88210

FORM APPROVED Budget Bureau No. 1004-0135 Expires March 31, 1993

SUBMIT IN TRIPLICATE 1. Type of Well		NA 7. If Unit or CA, Agreement Designation	
		NA	
		8. Well Name and No. WEST "B" #59	
		9. API Well No. 30-015-27318 10. Field and Pool, or Exploratory Area GRAYBURG-JACKSON 11. County or Parish, State EDDY CO., NEW MEXICO	
			CHECK APPROPRIATE BOX(s
TYPE OF SUBMISSION	TYPE OF ACTION	ON	
 Notice of Intent ∑ Subsequent Report 	Abandonment Recompletion	Change of Plans New Construction	
Final Abandonment Notice	Plugging Back Casing Repair Altering Casing	Non-Routine Fracturing Water Shut-Off Conversion to Injection	
	Other Spud & set surface csg	Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	
 Describe Proposed or Completed Operations (Clearly state all pe locations and measured and true vertical depths for all marker 	rtinent details, and give pertinent dates, including estimated date of starting as and zones pertinent to this work.)*	ny proposed work. If well is directionally drilled, give subsurface	
~ 1 11 . 4 4			
Spud well at 4:45 p. m on 10-10-94	14		
Spud well at 4:45 p. m on 10-10-94 Ran 8-5/8" surface csg as follows: 2 jts 8 5/8", 24 ppf, J-55, STC csg Float collar @ 522.58' 13 jts 8 5/8", 24 ppf, J-55, STC csg		OCT 24	
Ran 8-5/8" surface csg as follows: 2 jts 8 5/8", 24 ppf, J-55, STC csg Float collar @ 522.58" 13 jts 8 5/8", 24 ppf, J-55, STC csg Cmtd csg as follows:	6% D20 + 2% CaCl + 1/4 lb/sk D29 g Slurry yield = 1.93 cft/sx		
Ran 8-5/8" surface csg as follows: 2 jts 8 5/8", 24 ppf, J-55, STC csg Float collar @ 522.58' 13 jts 8 5/8", 24 ppf, J-55, STC csg Cmtd csg as follows: 165 sx 35/65 (Lite POZ; Class "C") + Slurry weight = 12.7 ppg 200 sx Class "C" + 2% CaCl	6% D20 + 2% CaCl + 1/4 lb/sk D29 g Slurry yield = 1.93 cft/sx		
Ran 8-5/8" surface csg as follows: 2 jts 8 5/8", 24 ppf, J-55, STC csg Float collar @ 522.58' 13 jts 8 5/8", 24 ppf, J-55, STC csg Cmtd csg as follows: 165 sx 35/65 (Lite POZ; Class "C") + Slurry weight = 12.7 ppg 200 sx Class "C" + 2% CaCl Slurry weight = 14.8 ppg Circulated 52 sx to pit	6% D20 + 2% CaCl + 1/4 lb/sk D29 g Slurry yield = 1.93 cft/sx g Slurry yield = 1.32 cft/sx	9 1994	
Ran 8-5/8" surface csg as follows: 2 jts 8 5/8", 24 ppf, J-55, STC csg Float collar @ 522.58' 13 jts 8 5/8", 24 ppf, J-55, STC csg Cmtd csg as follows: 165 sx 35/65 (Lite POZ; Class "C") + Slurry weight = 12.7 ppg 200 sx Class "C" + 2% CaCl Slurry weight = 14.8 ppg	6% D20 + 2% CaCl + 1/4 lb/sk D29 g Slurry yield = 1.93 cft/sx g Slurry yield = 1.32 cft/sx JO ANN HOOKS ENGINEERING TECHNICIAN	9 1994 37	