1 orm 3160-5 (June 1990)

Approved by_

Conditions of approval, if any:

UN ED STATES DEPARTMENT OF THE INTERIOR

| NM (| JIL | CONS | COMMISSIO |
|------|-----|------|-----------|
| Drav | wer | DD | |

Artesia, NM 88210

BUREAU OF LAND MANAGEMENT FORM APPROVED

| Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. | Expires March 31, 1993 use Designation and Serial No. |
|--|--|
| | 29426 A |
| | |
| 6. III | ndian, Allottee or Tribe Name |
| SUBMIT IN TRIPLICATE NA | |
| 7. If U | nit or CA, Agreement Designation |
| 1. Type of Well Soil Gas Other NA | |
| 2. Name of Operator | ll Name and No. |
| DEVON ENERGY OPERATING CORPORATION WES | T "A" #25 |
| | Well No. |
| 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405)552-4530 30-01 | 5-27369 |
| 4. Location of Well (Footage. Sec., T., R., M., or Survey Description) | ld and Pool, or Exploratory Area |
| 2625' FNL & 1335' FWL, Sec. 3-T17S-R31E GRAY | YBURG-JACKSON |
| 11. Co | ounty or Parish, State |
| EDDY | CO., NEW MEXICO |
| CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, O | R OTHER DATA |
| TYPE OF SUBMISSION TYPE OF ACTION | |
| Notice of Intent Abandonment Char | |
| | nge of Plans Construction |
| | -Routine Fracturing |
| | er Shut-Off |
| Maria Mari | version to Injection |
| (Note: Repo | ose Water ort results of multiple completion on Well |
| 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work | or Recompletion Report and Log form.) If well is directionally drilled, give subsurfa |
| locations and measured and true vertical depths for all markers and zones pertinent to this work.)* | |
| Spudded well @ 1:45 p. m. on 10/01/94. | |
| | |
| Ran 8-5/8" surface csg as follows: | |
| Guide shoe @ 623' | |
| 2 jts 8 5/8", 24 ppf, j-55, STC csg | |
| Float collar @ 530' | |
| 13 jts 8 5/8", 24 ppf, J-55, STC csg | 6.4 |
| Cmtd csg as follows: | The second secon |
| Cmtd csg as follows: 165 sx 35/65 (Lite POZ; Class "C") + 6% D20 + 2% CaCl + 1/4 lb/sk D29 | that it is the |
| Slurry weight = 12.7 ppg Slurry yield = 1.93 cft/sx | |
| 200 sx Class "C" + 2% CaCl NOV 5 199 | 14 |
| Slurry weight = 14.8 ppg Slurry yield = 1.32 cft/sx | 4 9 |
| | בע ר |
| Circulated 96 sx to pit CARLSBAD, NEW I | MEXICO . |
| 14. I hereby certify that the foregoing is true and correct | And the second s |
| KAREN ROSA ENGINEERING TECHNICIAN | |
| Signed Title Date (This space for Federal or State office use) | 11/10/94 |