Form 3160-5 (June 1990)

UI TED STATES DEPARTML: T OF THE INTERIOR

MM OIL CONS COMMISSION rawer DD

Artesia, NM FORM APPROVED **BUREAU OF LAND MANAGEMENT** Budget Bureau No. 1004-0135 Expires March 31, 1993

5. Lease Designation and Serial No.

Do not use this form for proposals to drill or	to deepen or reentry to a different reservoir. PERMIT—" for such proposals	reservoir. LC 029426 A 6. If Indian, Allottee or Tribe Name			
SUBMIT IN TRIPLICATE 1. Type of Well Solt Gas Well Other 2. Name of Operator DEVON ENERGY OPERATING CORPORATION 3. Address and Telephone No. 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405)552-4530 4. Location of Well (Footage. Sec., T., R., M., or Survey Description) 2625' FNL & 1335' FWL, Sec. 3-T17S-R31E		NA 7. If Unit or CA, Agreement Designation NA 8. Well Name and No. WEST "A" #25 9. API Well No. 30-015-27369 10. Field and Pool, or Exploratory Area			
			GRAYBURG-JACKSON 11. County or Parish, State EDDY CO., NEW MEXICO		
			CHECK APPROPRIATE BOX(s)	TO INDICATE NATURE OF NOTICE, REP	ORT, OR OTHER DATA
			Notice of Intent	TYPE OF ACTION Abandonment	Пан
		Subsequent Report	Recompletion Plugging Back	Change of Plans New Construction Non-Routine Fracturing	
Final Abandonment Notice	Casing Repair Altering Casing Other TD'd and set prod csg	Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well			
Describe Proposed or Completed Operations (Clearly state all pertino locations and measured and true vertical depths for all markers and true vertical depths for all markers and true vertical depths.)	ent details, and give pertinent dates, including estimated date of starting any p d zones pertinent to this work)*	Completion or Recompletion Report and Log form.) roposed work. If well is directionally drilled, give subsurface			
Reached TD 4380' on 10/7/94					
Ran 5-1/2" production csg as follows: 5 1/2 float shoe @ 4379' 1- jt 5 1/2" 15.5" csg 1- 5 1/2" float collar @ 4333'	18.04 0 1.4 4 4 4.4				
102 jts 5 1/2" 15.5# J-55 ST&C CS6 Cmtd csg as follows: 700 sx 35/65 (Lite POZ: Class "C") - (Slurry weight = 12.7 pps; slurry= 2.1	+ 6% Bentonite + 10% salt + 1/4 lb/sk cellophane fl	ake			
2425 sx Class "C" + 5% salt + 0.3% (Slurry weight 14.8 pps; slurry = 1.30 Circulated 165 sx cmt to surface	059 fluid loss + 1/4 lb/sk cellophane flake	CEPTED FOR RECU生			
	CA	NOV 15 1994			
14. I hereby certify that the foregoing is true and correct Signed Karlm Rosa	KAREN ROSA ENGINEERING TECHNICIAN	Date 11/10/94			
(This space for Federal or State office use)	THE	Date ANALYT			
Approved by	Title	Date			