Form 3160-5 (June 1990)

UNTED STATES DEPARTME. I OF THE INTERIOR BUREAU OF LAND MANAGEMENT

NM OIL CONS COMMISSIUN
Drawer DD
NM 88210
Art 40KM APPROVED
Budget Bureau No. 1004-0135

Budget Bureau No. 1004-0135
Expires March 31, 1993

S. Leas Designation and Social No.

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals SUBMIT IN TRIPLICATE 1. Type of Well Well Gas Well Other 2. Name of Operator DEVON ENERGY OPERATING CORPORATION 3. Address and Telephone No. 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405)552-4530 4. Location of Well (Footage. Sec., T., R., M., or Survey Description) 15' FNL & 2625' FEL, Sec. 9-T17S-R31E		 Lease Designation and Serial No. LC 029426 B
		6. If Indian, Allottee or Tribe Name
		NA 7. If Unit or CA, Agreement Designation
		NA
		8. Well Name and No.
		WEST "B" #64
		9. API Well No. 30-015-
		10. Field and Pool, or Exploratory Area
		GRAYBURG-JACKSON 11. County or Parish, State
		EDDY CO., NEW MEXICO
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPO	ORT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent	Abandonment Recompletion	Change of Plans New Construction
Subsequent Report	Plugging Back	Non-Routine Fracturing
Final Abandonment Notice	Casing Repair Altering Casing	Water Shut-Off
Piliai Abalidolitielii Nolice	Other Spud & set surface csg	Conversion to Injection Dispose Water
		(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
Describe Proposed or Completed Operations (Clearly state all per locations and measured and true vertical depths for all marker.	tinent details, and give pertinent dates, including estimated date of starting any pr	oposed work. If well is directionally drilled, give subsurface
locations and measured and true ventical deputs for all markers	s and zones perunent to this work.	
Spudded well @ 2:30 p.m. on 11/8/94.	ACCEPTED FOR RECO	
Ran surface csg as follows: Guide shoe @ 575' 2 jts 8 5/8" 24 ppf, J-55, 8rd ST&6 Float collar @ 486' 11 jts 8 5/8", 24 ppf, J-55, 8rd ST&6	CARLSBAD, NEW MEXIC	
Cemented csg as follows:		(1)
165 sx 35/65 POZ; Class "C" + 69	% D20 + 2% SI + ¼ lb/sk D-29	
(Slurry Weight = 12.7 ppg	6 D20 + 2% SI + 1/4 lb/sk D-29 , Slurry Yield 1.93 cft/sk)	EE CO
225 sx Class "H" + 2% S1		t.C.
(Slurry Weight = 14.8 ppg Circulated 91 sx to surface.	·	
Circulated 91 sx to surface.		
14. I hereby certify that the foregoing is true and correct	VADDA SOC.	
Signed Karen Rosa	KAREN ROSA ENGINEERING TECHNICIAN	Date 11/10/94
This space for Federal or State office use)		
Approved by	Title	Date
Conditions of approval, if any:		