

RECEIVED

458

Form 3160-5
(June 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

DEC 08 1993

NM OIL CONS COMMISSION

Drawer DD FORM APPROVED

Budget Bureau No. 1001 0135
Artesia, NM 88211-0135

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Anadarko Petroleum Corporation

3. Address and Telephone No.
PO Drawer 130, Artesia, NM 88211-0130 (505) 677-2411

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

(At surface) 1400' FSL & 660' FEL, Sec 26, T17S, R30E
(At 11372') 667' FSL & 657' FEL, Sec 26, T17S, R30E

5. Lease Designation and Serial No.

LC 030570b

6. If Indian, Allottee or Tribe Name

7. If Unit or C/A, Agreement Designation

8. Well Name and No.

Power Federal Com #2

9. API Well No.

30-015-27508

10. Field and Pool, or Exploratory Area

Cedar Lake Morrow

11. County or Parish, State

Eddy, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Run 4 1/2" csg & cement

- ☐ Change of Plans
☐ New Construction
☐ Non Routine Fracturing
☐ Water Shut Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

1. Resumed drlg with 7 7/8" bit on 09-26-93.
2. Drilled to 6406' and Yellow Jacket Test BOP to 3000#; OK.
3. Drilled to 7000' and started directional drilling to target area. Dig multi shot survey, found bottom of hole 616.21' FSL & 663.19' FEL. Measured depth of 11,560' and TVD 11,417.71'. See attached D.I.G.'s Inc. directional survey.
4. Reached depth of 11,530', 10-28-93. RU loggers couldn't get below 11,256', TOH with logging tool. RD logger. TIH with bit and scraper to 11,530'. TOH.
5. RU HLS and logged with Spectral Density Log TD to csg shoe and Dual Spectral neutron / GR TD - to surface. Ran Dual Laterolog Micro-SFL Log from 11,402' - 3496'. Couldn't get below 11,402' with logging tool. TON with L. Tool RDHLS.
6. TIH with bit and drilled new hole 11,530' - 11,560' while WOO. Dropped Multi-shot Survey Tool. TOH with bit to 7000'. Pulled Multi-shot Tool. Resumed TOH, laying down drill pipe.

Cont'd page 2.

14. I hereby certify that the foregoing is true and correct

Signed Howard Hoke
(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title Field Foreman
ACCEPTED FOR RECORD

Title (ORIG. SGD) DAVID R. GLASS
DEC 7 1993

Date 11-23-93

Date _____

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instructions on Reverse Side

7. TIH with 279 jts of 4½" 11.6# S-95 R-3 csg with float shoe and float collar, DV tool and 15 centralizers. Set float shoe at 11,551' KB set, set float collar at 11,509' KB and set DV tool at 7997' KB. Ran centralizers on middle of 1st jt, on 4th jt, 7, 10, 21, 24, 27, 37, 40, 84, 86, 159, 190, 194 and 2nd jt down from surface. Ruff coated pipe 4 jts 11,422' - 11,254', 6 jts 10,667' - 10,415', and 2 jts 10,004' - 9919'.
8. RU Halliburton and pumped 23.8 bbls Super Flush 102 and cemented 1st stage with 475 sx Lead cement. (Halliburton Lite Premium with ¼#/sx Flocele, 4/10 of 1% Halad 322). Tailed in with 245 sx Premium cement with 3/10 CFR-3, 5/10 Halad 22A and 4# KCL/sx. Plug down at 11:40 p.m., 10-31-93. Held OK. Dropped bomb and opened DV tool with 900# PSI. Started circ thru DV tool for 6 hrs. Circ 215 sx cement to pit. 2nd stage cementing - pumped 910 sx Halliburton Lite Premium with ¼# Flocele and 4/10 of 1% Halad 322. Tailed in with 200 sx Premium Heat cement. Plug down at 7:20 a.m., 11-01-93. Held OK. Did not circ cement.
9. Ran Temp Survey. Found cement top at 1750' from surface. Nippled down. Set 4½" csg slips. Cut off 4½" csg and released rig at 9:00 p.m., NM, 11-01-93

D.I.G. INC.

ANADARKO PETROLEUM CORP.
POWER FEDERAL #2
EDDY COUNTY, N.M.

Calculated by Minimum Curvature Method
Vert Sect Plane: S 0.00 E

- RECORD OF SURVEY -

MEASURED DEPTH (FT)	INCL ANGLE (DEG)	D R I F T DIRECTION (DEG)	COURSE LENGTH (FT)	TRUE VERTICAL DEPTH	T O T A L RECTANGULAR COORDINATES (FT)		VERTICAL SECTION (FT)	C L O S U R E DISTANCE DIRECTION (FT) (DEG)		DOGLEG SEVERITY (DD/100')
0.00	0.00	N 0.00 E	0.00	0.00	0.00	N 0.00 E	0.00	0.00	N 0.00 E	0.00
100.00	1.00	S 70.00 W	100.00	99.99	0.30	S 0.82 W	0.30	0.87	S 70.00 W	1.00
200.00	1.50	S 67.00 W	100.00	199.97	1.11	S 2.84 W	1.11	3.05	S 68.71 W	0.50
300.00	1.00	S 65.00 W	100.00	299.95	1.99	S 4.84 W	1.99	5.23	S 67.67 W	0.50
400.00	1.75	N 68.00 W	100.00	399.92	1.79	S 7.05 W	1.79	7.27	S 75.78 W	1.29
500.00	1.75	N 62.00 W	100.00	499.87	0.50	S 9.81 W	0.50	9.82	S 87.10 W	0.18
600.00	2.00	N 58.00 W	100.00	599.82	1.15	N 12.64 W	-1.15	12.69	N 84.82 W	0.78
700.00	2.00	N 58.00 W	100.00	699.76	2.99	N 15.80 W	-2.99	15.88	N 79.13 W	0.00
800.00	1.75	N 57.00 W	100.00	799.71	4.75	N 18.36 W	-4.75	18.96	N 75.49 W	0.25
900.00	1.50	N 57.00 W	100.00	899.66	6.30	N 20.74 W	-6.30	21.67	N 73.11 W	0.25
1000.00	1.25	N 57.00 W	100.00	999.64	7.60	N 22.75 W	-7.60	23.99	N 71.52 W	0.25
1100.00	1.00	N 40.00 W	100.00	1099.62	8.86	N 24.23 W	-8.86	25.80	N 69.90 W	0.41
1200.00	1.50	N 7.00 W	100.00	1199.59	10.83	N 24.95 W	-10.83	27.20	N 66.53 W	0.86
1300.00	1.25	N 11.00 E	100.00	1299.57	13.20	N 24.90 W	-13.20	28.18	N 62.06 W	0.50
1400.00	1.00	N 10.00 E	100.00	1399.55	15.13	N 24.54 W	-15.13	28.83	N 58.34 W	0.25
1500.00	1.25	N 9.00 W	100.00	1499.53	17.07	N 24.56 W	-17.07	29.91	N 55.20 W	0.45
1600.00	1.50	N 16.00 W	100.00	1599.50	19.40	N 25.09 W	-19.40	31.72	N 52.28 W	0.30
1700.00	1.50	N 28.00 W	100.00	1699.46	21.82	N 26.06 W	-21.82	33.99	N 50.07 W	0.31
1800.00	1.50	N 8.00 W	100.00	1799.43	24.27	N 26.86 W	-24.27	36.20	N 47.90 W	0.52
1900.00	1.50	N 12.00 W	100.00	1899.40	26.85	N 27.31 W	-26.85	38.30	N 45.50 W	0.10
2000.00	1.25	N 30.00 W	100.00	1999.37	29.07	N 28.13 W	-29.07	40.45	N 44.06 W	0.50
2100.00	1.50	N 33.00 W	100.00	2099.34	31.11	N 29.39 W	-31.11	42.80	N 43.37 W	0.26
2200.00	1.50	N 32.00 W	100.00	2199.30	33.32	N 30.80 W	-33.32	45.37	N 42.75 W	0.03
2300.00	2.00	N 28.00 W	100.00	2299.26	35.97	N 32.31 W	-35.97	48.35	N 41.93 W	0.51
2400.00	2.00	N 26.00 W	100.00	2399.20	39.08	N 33.89 W	-39.08	51.73	N 40.93 W	0.07
2500.00	2.75	N 3.00 W	100.00	2499.13	42.61	N 34.76 W	-42.61	54.99	N 39.21 W	0.88
2600.00	2.00	N 3.00 E	100.00	2599.06	46.31	N 34.77 W	-46.31	57.91	N 36.90 W	0.33
2700.00	1.50	N 5.00 E	100.00	2699.01	49.36	N 34.57 W	-49.36	60.76	N 35.00 W	0.50
2800.00	1.50	N 9.00 W	100.00	2798.98	51.96	N 34.66 W	-51.96	62.45	N 33.71 W	0.37
2900.00	1.50	N 11.00 W	100.00	2898.95	54.53	N 35.11 W	-54.53	64.86	N 32.78 W	0.05
3000.00	1.50	N 11.00 W	100.00	2998.91	57.10	N 35.61 W	-57.10	67.30	N 31.95 W	0.00
3100.00	1.50	N 11.00 W	100.00	3098.88	59.67	N 36.11 W	-59.67	69.75	N 31.18 W	0.00

Survey Ref: Well Head Closure Ref: Well Head
Mon Nov 01 1993 12:51:53

Vert Sect Ref: Well Head
File: ANADARP2.DAT

Page 1

D.I.G. INC.

ANADARKO PETROLEUM CORP.
POWER FEDERAL #2
EDDY COUNTY, N.M.

Calculated by Minimum Curvature Method
Vert Sect Plane: S 0.00 E

- RECORD OF SURVEY -

MEASURED DEPTH (FT)	INCL ANGLE (DEG)	D R I F T DIRECTION (DEG)	COURSE LENGTH (FT)	TRUE VERTICAL DEPTH	T O T A L RECTANGULAR COORDINATES (FT)		VERTICAL SECTION (FT)	C L O S U R E DISTANCE DIRECTION (FT) (DEG)		DOGLEG SEVERITY (DG/100')
3200.00	1.50	N 4.00 W	100.00	3198.84	62.74 N	36.45 W	-62.26	72.15	N 30.35 W	0.18
3300.00	1.25	N 1.00 W	100.00	3298.81	64.66 N	36.56 W	-64.66	74.28	N 29.49 W	0.26
3400.00	1.50	N 1.00 W	100.00	3398.79	67.06 N	36.60 W	-67.06	76.40	N 28.63 W	0.25
3500.00	1.50	N 2.00 W	100.00	3498.75	69.67 N	36.67 W	-69.67	78.74	N 27.76 W	0.03
3600.00	1.25	N 3.00 W	100.00	3598.72	72.07 N	36.78 W	-72.07	80.91	N 27.03 W	0.25
3700.00	1.75	N 7.00 W	100.00	3698.69	74.68 N	37.02 W	-74.68	83.35	N 26.37 W	0.51
3800.00	2.00	N 4.00 W	100.00	3798.63	77.93 N	37.33 W	-77.93	86.41	N 25.59 W	0.27
3900.00	2.25	N 2.00 E	100.00	3898.57	81.64 N	37.38 W	-81.64	89.79	N 24.60 W	0.33
4000.00	2.00	N 14.00 E	100.00	3998.50	85.29 N	36.89 W	-85.29	92.93	N 23.39 W	0.51
4100.00	2.00	N 11.00 E	100.00	4098.44	88.70 N	36.13 W	-88.70	95.77	N 22.17 W	0.10
4200.00	1.75	N 3.00 E	100.00	4198.38	91.93 N	35.72 W	-91.93	98.63	N 21.23 W	0.36
4300.00	2.00	N 16.00 E	100.00	4298.33	95.14 N	35.16 W	-95.14	101.43	N 20.28 W	0.49
4400.00	2.00	N 2.00 W	100.00	4398.27	98.56 N	34.74 W	-98.56	104.50	N 19.42 W	0.63
4500.00	2.25	N 1.00 E	100.00	4498.20	102.26 N	34.77 W	-102.26	108.01	N 18.78 W	0.27
4600.00	2.25	N 6.00 W	100.00	4598.12	106.18 N	34.94 W	-106.18	111.78	N 18.21 W	0.27
4700.00	2.25	N 10.00 E	100.00	4698.05	110.07 N	34.80 W	-110.07	115.44	N 17.55 W	0.63
4800.00	1.50	N 3.00 W	100.00	4797.99	113.31 N	34.53 W	-113.31	118.45	N 16.95 W	0.86
4900.00	2.25	N 16.00 W	100.00	4897.94	116.50 N	35.14 W	-116.50	121.68	N 16.78 W	0.86
5000.00	2.25	N 26.00 W	100.00	4997.86	120.15 N	36.54 W	-120.15	125.58	N 16.92 W	0.39
5100.00	2.75	N 24.00 W	100.00	5097.77	124.11 N	38.38 W	-124.11	129.90	N 17.18 W	0.51
5200.00	2.25	N 27.00 W	100.00	5197.67	128.05 N	40.24 W	-128.05	134.22	N 17.45 W	0.52
5300.00	2.25	N 33.00 W	100.00	5297.60	131.44 N	42.20 W	-131.44	138.05	N 17.80 W	0.24
5400.00	2.75	N 42.00 W	100.00	5397.50	134.87 N	44.88 W	-134.87	142.14	N 18.41 W	0.63
5500.00	3.00	N 32.00 W	100.00	5497.37	138.87 N	47.87 W	-138.87	146.89	N 19.02 W	0.56
5600.00	2.75	N 31.00 W	100.00	5597.25	143.15 N	50.49 W	-143.15	151.79	N 19.43 W	0.25
5700.00	3.00	N 34.00 W	100.00	5697.12	147.37 N	53.19 W	-147.37	156.88	N 19.85 W	0.29
5800.00	2.50	N 39.00 W	100.00	5797.01	151.24 N	56.03 W	-151.24	161.28	N 20.33 W	0.55
5900.00	2.75	N 35.00 W	100.00	5896.90	154.90 N	58.78 W	-154.90	165.68	N 20.78 W	0.31
6000.00	2.50	N 42.00 W	100.00	5996.80	158.49 N	61.61 W	-158.49	170.04	N 21.24 W	0.41
6100.00	3.00	N 42.00 W	100.00	6096.68	162.05 N	64.82 W	-162.05	174.53	N 21.80 W	0.50
6200.00	2.50	N 38.00 W	100.00	6196.57	165.71 N	67.92 W	-165.71	179.09	N 22.29 W	0.54
6300.00	2.75	N 42.00 W	100.00	6296.46	169.22 N	70.86 W	-169.22	183.45	N 22.72 W	0.31
6400.00	2.50	N 40.00 W	100.00	6396.36	172.67 N	73.87 W	-172.67	187.81	N 23.16 W	0.27

Survey Ref: Well Head Closure Ref: Well Head
Mon Nov 01 1993 12:51:53

Vert Sect Ref: Well Head
File: ANADARP2.DAT

Page 2

D.I.G. INC.

ANADARKO PETROLEUM CORP.
POWER FEDERAL #2
EDDY COUNTY, N.M.

Calculated by Minimum Curvature Method
Vert Sect Plane: S 0.00 E

- RECORD OF SURVEY -

MEASURED DEPTH (FT)	INCL ANGLE (DEG)	D R I F T DIRECTION (DEG)	COURSE LENGTH (FT)	TRUE VERTICAL DEPTH	T O T A L RECTANGULAR COORDINATES (FT)		VERTICAL SECTION (FT)	C L O S U R E DISTANCE DIRECTION (FT) (DEG)		DOGLEG SEVERITY (DG/100')
6500.00	3.00	N 27.00 W	100.00	6496.24	176.67 N	76.46 W	-176.67	192.51	N 23.40 W	0.80
6600.00	3.00	N 22.00 W	100.00	6596.11	181.43 N	78.63 W	-181.43	197.73	N 23.43 W	0.76
6700.00	3.00	N 15.00 W	100.00	6695.97	186.38 N	80.29 W	-186.38	202.94	N 23.30 W	0.37
6800.00	2.50	N 14.00 W	100.00	6795.85	191.03 N	81.49 W	-191.03	207.68	N 23.10 W	0.50
6978.00	3.43	N 30.57 W	178.00	6973.62	199.38 N	85.14 W	-199.38	216.80	N 23.12 W	0.71
7073.00	5.42	N 46.46 W	95.00	7068.33	204.92 N	89.84 W	-204.92	223.74	N 23.67 W	2.44
7167.00	4.98	N 57.38 W	94.00	7161.95	210.17 N	96.49 W	-210.17	231.27	N 24.66 W	1.15
7261.00	3.48	S 84.09 W	94.00	7255.71	212.08 N	102.77 W	-212.08	235.67	N 25.85 W	3.33
7356.00	3.23	S 49.58 W	95.00	7350.55	210.05 N	107.67 W	-210.05	236.04	N 27.14 W	2.11
7450.00	4.02	S 20.53 W	94.00	7444.37	205.24 N	110.85 W	-205.24	233.26	N 28.37 W	2.10
7545.00	4.59	S 21.62 W	95.00	7539.10	198.59 N	113.41 W	-198.59	228.70	N 29.73 W	0.61
7639.00	6.10	S 11.92 W	94.00	7632.69	190.21 N	115.83 W	-190.21	222.70	N 31.34 W	1.87
7733.00	7.28	S 4.05 W	94.00	7726.05	179.38 N	117.28 W	-179.38	214.32	N 33.18 W	1.59
7828.00	8.06	S 5.57 W	95.00	7820.20	166.75 N	118.36 W	-166.75	204.48	N 35.37 W	0.85
7922.00	8.83	S 6.74 W	94.00	7913.18	153.02 N	119.84 W	-153.02	194.37	N 38.07 W	0.84
8017.00	9.34	S 5.54 W	95.00	8006.99	138.11 N	121.44 W	-138.11	183.91	N 41.33 W	0.57
8111.00	10.39	S 3.84 W	94.00	8099.60	122.06 N	122.75 W	-122.06	173.10	N 45.16 W	1.16
8205.00	11.55	S 10.70 E	94.00	8191.90	104.35 N	121.57 W	-104.35	160.21	N 49.36 W	3.18
8300.00	14.53	S 19.08 E	95.00	8284.44	83.49 N	116.70 W	-83.49	143.49	N 54.42 W	3.30
8394.00	15.90	S 14.52 E	94.00	8375.14	59.64 N	110.40 W	-59.64	125.48	N 61.62 W	1.47
8489.00	17.02	S 15.58 E	95.00	8466.25	33.65 N	103.41 W	-33.65	108.74	N 71.97 W	1.22
8583.00	18.23	S 16.71 E	94.00	8555.84	6.32 N	95.48 W	-6.32	95.69	N 86.21 W	1.34
8677.00	19.53	S 14.88 E	94.00	8644.78	22.95 S	87.22 W	22.95	90.19	S 75.26 W	1.52
8772.00	21.70	S 15.92 E	95.00	8733.69	55.19 S	78.32 W	55.19	95.82	S 54.83 W	2.32
8866.00	22.72	S 15.19 E	94.00	8820.71	89.42 S	68.80 W	89.42	112.83	S 37.57 W	1.12
8961.00	20.89	S 15.61 E	95.00	8908.91	123.44 S	59.43 W	123.44	137.01	S 25.71 W	1.93
9055.00	19.05	S 15.13 E	94.00	8997.26	154.40 S	50.92 W	154.40	162.58	S 18.25 W	1.97
9150.00	14.35	S 15.09 E	95.00	9088.23	180.74 S	43.80 W	180.74	185.98	S 13.62 W	4.95
9244.00	10.57	S 12.69 E	94.00	9180.00	200.41 S	38.88 W	200.41	204.14	S 10.98 W	4.06
9338.00	11.53	S 12.10 E	94.00	9272.25	218.01 S	35.01 W	218.01	220.80	S 9.12 W	1.03
9432.00	12.74	S 13.49 E	94.00	9364.15	237.27 S	30.63 W	237.27	239.24	S 7.35 W	1.32
9527.00	13.12	S 11.77 E	95.00	9456.74	258.01 S	25.98 W	258.01	259.32	S 5.75 W	0.57
9621.00	15.89	S 7.85 E	94.00	9547.74	281.21 S	22.05 W	281.21	282.07	S 4.48 W	3.12

Survey Refs Well Head Closure Refs Well Head
Mon Nov 01 1993 12:51:53

Vert Sect Refs Well Head
File: ANADARP2.DAT

Page 3

D.I.G. INC.

ANADARKO PETROLEUM CORP.
POWER FEDERAL #2
EDDY COUNTY, N.M.

Calculated by Minimum Curvature Method
Vert Sect Plane: S 0.00 E

- RECORD OF SURVEY -

MEASURED DEPTH (FT)	INCL ANGLE (DEG)	D R I F T DIRECTION (DEG)	COURSE LENGTH (FT)	TRUE VERTICAL DEPTH	T O T A L RECTANGULAR COORDINATES (FT)		VERTICAL SECTION (FT)	C L O S U R E DISTANCE DIRECTION (FT) (DEG)		DOGLEG SEVERITY (DD/100')
9715.00	13.54	S 3.36 E	94.00	9638.65	304.92	S 19.26 W	304.92	305.52	S 3.61 W	2.59
9810.00	11.58	S 4.26 E	95.00	9731.37	325.30	S 17.51 W	325.50	325.97	S 3.08 W	2.08
9904.00	13.96	S 0.64 W	94.00	9823.04	346.25	S 16.94 W	346.25	346.66	S 2.80 W	2.78
9998.00	16.16	S 3.84 W	94.00	9913.81	370.64	S 17.94 W	370.64	371.08	S 2.77 W	2.50
10093.00	14.05	S 6.93 W	95.00	10003.52	395.29	S 20.14 W	395.29	395.81	S 2.92 W	2.34
10187.00	12.70	S 4.98 W	94.00	10096.97	416.92	S 22.34 W	416.92	417.52	S 3.07 W	1.49
10281.00	13.62	S 3.70 E	94.00	10188.51	438.26	S 22.52 W	438.26	438.84	S 2.94 W	2.32
10375.00	16.15	S 9.13 E	94.00	10279.36	462.22	S 19.73 W	462.22	462.64	S 2.44 W	3.07
10470.00	18.23	S 14.06 E	95.00	10370.11	489.69	S 14.02 W	489.69	489.89	S 1.64 W	2.67
10564.00	16.53	S 12.93 E	94.00	10459.82	516.98	S 7.46 W	516.98	517.04	S 0.83 W	1.84
10658.00	16.29	S 12.72 E	94.00	10549.99	542.88	S 1.56 W	542.88	542.88	S 0.16 W	0.26
10753.00	13.64	S 11.10 E	95.00	10641.76	566.87	S 3.53 E	566.87	566.88	S 0.36 E	2.82
10847.00	12.20	S 12.36 E	94.00	10733.38	587.45	S 7.79 E	587.45	587.50	S 0.74 E	1.56
10941.00	13.29	S 12.25 E	94.00	10825.06	607.71	S 12.21 E	607.71	607.83	S 1.15 E	1.16
11036.00	15.53	S 12.09 E	95.00	10917.06	630.82	S 17.19 E	630.82	631.05	S 1.56 E	2.36
11130.00	18.30	S 13.55 E	94.00	11006.99	657.48	S 23.28 E	657.48	657.89	S 2.03 E	2.98
11224.00	19.29	S 10.92 E	94.00	11095.98	687.07	S 29.68 E	687.07	687.71	S 2.47 E	1.39
11318.00	17.63	S 9.62 E	94.00	11185.14	716.35	S 33.00 E	716.35	717.21	S 2.80 E	1.82
11413.00	15.92	S 8.92 E	95.00	11276.09	743.41	S 39.43 E	743.41	744.45	S 3.04 E	1.81
11507.00	15.39	S 4.82 E	94.00	11366.61	768.58	S 42.48 E	768.58	769.75	S 3.16 E	1.30
11535.00	15.36	S 4.75 E	28.00	11393.60	775.97	S 43.09 E	775.97	777.17	S 3.18 E	0.13
11560.00	15.37	S 4.78 E	25.00	11417.71	782.57	S 43.64 E	782.57	783.79	S 3.19 E	0.05

Survey Ref: Well Head Closure Ref: Well Head
Mon Nov 01 1993 12:51:53

Vert Sect Ref: Well Head
File: ANADARP2.DAT

Page 6