

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):				38. GEOLOGIC MARKERS		
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	MEAS. DEPTH	TRUE VERT. DEPTH
Rustler	305	520	ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.. (continued from the front)			
Salado	520	1340				
Tansill	1340	1496				
Yates	1496	1794				
Seven Rivers	1794	2406				
Queen	2406	2818				
(Artesia)						
Grayburg	2818	3130				
San Andres	3130	3988 (TD)				
		DEPTH				
		3177'-3296	Acidized w/2150 gals 15% HCl acid. Frac'd w/17,000 gals gel + 44,000# Brady sand + 11,000# SLC resin coated sand.			
		2989'-3127'	Acidized w/1650 gals 15% HCl acid.			
		2877'-2956'	Acidized w/1000 gals 15% HCl acid.			
		2877'-3127'	Frac'd w/30,000 gals gel + 85,000# Brady sand + 32,000# resin coated sand.			