Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

NM OIL CONS COMMISSION Drawer DD

Artesia, NM 88210

FORM APPROVED

Budget Bureau No. 1004-0135
Expires March 31, 1993

5. Lease Designation and Serial No.

SUNDRY NOTICES	AND REPORTS ON WELLS	5. Lease Designation	on and Serial No.	
Do not use this form for proposals to drill or to deepen or reentry to a different reservoir		r. LC-029435-A		
Use "APPLICATION FOR PERMIT—" for such proposals		6. If Indian, Allotte	e or Tribe Name	
SUBMIT IN TRIPLICATE		NA		
Type of Well Oil Oil Other Name of Operator DEVON ENERGY OPERATING CORPORATION 3. Address and Telephone No. 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405)552-4530		7. If Unit or CA, Agreement Designation NA 8. Well Name and No. Fedural		
		30-015- 28047		
		4. Location of Well (Footage. Sec., T., R., M., or Survey Description) 1300' FNL & 60' FEL, Sec. 7-T17S-R31E		10. Field and Pool,
Grayburg-Jackson 11. County or Parish, State				
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, F	REPORT, OR OTHE	R DATA	
TYPE OF SUBMISSION	TYPE OF ACT	TON		
Notice of Intent	Abandonment	Change of Plans		
	Recompletion	New Construction	n	
Subsequent Report	Plugging Back	Non-Routine Fra	cturing	
F1	Casing Repair	Water Shut-Off		
Final Abandonment Notice	Altering Casing	Conversion to Inj	ection	
	Other TD'd & set prod csg	Dispose Water (Note: Report results of mai		
13 Describe Proposed or Completed Operations (Clearly state all per	tinent details, and give pertinent dates, including estimated date of startin	Completion or Recompletion or		
locations and measured and true vertical depths for all marker		• 7	(,	
TD 4010' on 12/7/94.		: 1		
	a di kacamatan di Kabupatèn Kabupatèn Kabupatèn Kabupatèn Kabupatèn Kabupatèn Kabupatèn Kabupatèn Kabupatèn Ka Kabupatèn Kabupatèn		Æ	
Ran 5 1/2" prod csg as follows:				• •
Guide shoe @ 4009'		:	•••	- 1 * 1
1 jt 5 1/2", 15.5 ppf, J-55, 8rd LT&C csg		<i>5</i> 35	š	(3)
Float collar @ 3969'			1 :	5 77
93 jts 5 1/2", 15.5 ppf, J-55, 8rd LT&C csg		ال المستعدد		
Cemented csg as follows:				
	% D-20 + 10% D-44 + 1/4 lb/sk D-29 + .2%	D-4 6		
` , ,	2.7 lbs/gal Slurry yield = 2.1 cft/sk)			
350 sx "C" + 5% D-44 + .3% D-59 + 1/4 lb/sk D-29				
, , ,	4.8 lbs/gal Slurry yield = 1.36 cft/sk)			
Did not circ cmt. We plan to pun	np in and circ cmt to surface via 1" tbg before	ore completing well.	TOC @ 440) '.
14. I hereby certify that the foregoing is true and correct	KAREN ROSA			
Signed Koran Rosa Title ENGINEERING TECHNICL		Date 1/2/95		
(This space for Federal or State office use)				
A	Title	Dete		
Approved by	Title	Date		