

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):				38. GEOLOGIC MARKERS		
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	MEAS. DEPTH	TRUE VERT. DEPTH
Rustler	340	528	ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.. (continued from the front)			
Salado	528	1358				
Tansill	1358	1512				
Yates	1512	1812				
Seven Rivers	1812	2427				
Queen	2427	2836				
(Artesia)						
Grayburg	2836	3149				
San Andres	3149	4010 (TD)				
		DEPTH				
		3477'-3684'	Acidized w/2500 gals 15% HCl acid. Frac'd w/23,000 gals gel + 65,500# 20/40 Brady sand + 20,000# resin coated sand.			
		3198'-3314'	Acidized w/1625 gals 15% HCl acid. Reperf'd and acidized w/1625 gals 15% HCl acid.			
		2971'-3147'	Acidized w/2200 gals 15% HCl acid. Frac'd w/50,000 gals gel + 133,000# 20/40 Brady sand + 32,000# resin coated sand.			