	INT	₽₽D STATES	NM OIL CONS CUMPILOUT Drawer DD NM 88210	
Form 3160-5 (June 1990)		OF THE INTERIOR		
(. uk 1990)			Drawer DD Artesia, NM 88210 C(>'	
	BUREAU OF I	AND MANAGEMENT	Budget Bureau No. 1004-0135 Expires March 31, 1993	
	SUNDRY NOTICES	AND REPORTS ON WELLS	5. Lease Designation and Serial No.	
Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals			r. LC-029435-A	
			6. If Indian, Allottee or Tribe Name	
			NA	
			7. If Unit or CA, Agreement Designation	
1. Type of Well Ø Oil Well Well Other			NA	
2. Name of Operator DEVON ENERGY OPERATING CORPORATION			8. Well Name and No. J. L. Keel "A" # 18	
3. Address and Telephone 1	No		9. API Well No.	
20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405)552-4527			30-015-28078	
4. Location of Well (Footage. Sec., T., R., M., or Survey Description)			10. Field and Pool, or Exploratory Area	
1310' FNL & 1100' FWL, Sec. 7-T17S-R31E			Grayburg-Jackson 11. County or Parish, State	
			Eddy Co., NM	
	·			
CHECK AF	PROPRIATE BOX(s	) TO INDICATE NATURE OF NOTICE, F	REPORT, OR OTHER DATA	
TYPE OF SU	IBMISSION	TYPE OF ACTION		
Notice of Intent		Abandonment	Change of Plans	
		Recompletion	New Construction - 23	
Subsequent Report		Plugging Back	Non-Routine Fracturing	
_		Casing Repair	Water Shut-Off	
Final Abandonment No	otice	Altering Casing	Conversion to Injection	
		Other Perf'd acidized & frac'd	(Note: Report results of multiple completion on Well (")	
			Completion or Recompletion Report Constraints of Web ()	
	and true vertical depths for all marker			
2/7/95-2/9	Jackson 3447'-3-	laughter 3625'-3670', the Lower Jackson 499' w/1 SPF (2240" holes). The Slau	ghter and Lower Jackson zones were	
		gals 15% HCl acid. The Middle Jackson		
	acid. The Slaugh	nter thru the Middle Jackson 3447'-3670'	was frac'd w/31,500 gals gel +	
	77,000# 20/40 B	ater thru the Middle Jackson 3447'-3670' and sand + 24,000# resin coated sand	CEIVEN	
2/24/95-2/	27/95 - We perf'd the	Grayburg 2865'-3089 and Vacuum 3232	3135' w/1 SPF (1740" holes).	
	Additional perfs	were shot within the Grayburg and Vacuu	fin intervalig40" holes). These	
	zones were acidi	zed w/2825 gals 15% HCl acid. The inter	val was frac'd w/37,500 gal $+ 92,000 \#$	
	20/40 Brady san	zed w/2825 gals 15% HCl acid. The inter 1 + 32,000# resin coated sand.	COM Days	
	20, 10 Drudy build			
		Li di la constante di la consta	Dist. 2	
14. I hereby certify that the	foregoing is true and correct			
Dan	Para	KAREN ROSA ENGINEERING TECHNICIAN		
Signed <u>C</u> <u>C</u> <u>C</u> <u>Signed</u> <u>C</u>	1 Min Da	Title	Date <u>4/3/95</u>	
(This space for Federal or St	LALE OTHER USC)			
Approved by Conditions of approval, if ar	n.v.	Title	Date	
wannons of approval, if an	цу.			
Title 18 U.S.C. Section 1001, m	akes it a crime for any person knowin	gly and willfully to make to any department or agency of the United State	any false, fictitious or fraudulent statements or representations as to	
any matter within its jurisdiction			· · · · · · · · · · · · · · · · · · ·	