Form 3160-5 (June 1990)

Approved by_

Conditions of approval, if any:

UNTED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

Drawer DD Artesia, NM 88210 OIST

FORM APPROVED

| | | Expires March 31, 1993 |
|--|--|--|
| SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals | | 5. Lease Designation and Serial No. |
| | | LC 029435-B |
| | | 6. If Indian, Allottee or Tribe Name |
| SUBMIT | IN TRIPLICATE | J NA |
| I. Type of Well | | 7. If Unit or CA, Agreement Designation |
| ⊠ OI ☐ Gas ☐ Other Well | A 4255 | NA |
| 2. Name of Operator DEVON ENERGY OPERATING CORPORA | JACK 7 4 1880 | 8. Well Name and No. |
| | | J. L. Keel "B" #56 |
| 3. Address and Telephone No. 20 NORTH BROADWAY, SUITE 1600, OKLAHOMA CITY, OKLAHOMA 73102 (405)552-4530 | | 9. API Well No. |
| 4. Location of Well (Footage, Sec., T., R., M., or Survey D | ecription) | 10. Field and Pool, or Exploratory Area |
| | - · | Grayburg Jackson |
| 1280' FNL & 1300' FWL, Sec. 8-T17S-R31E | | 11. County or Parish, State |
| | | |
| | , | Eddy Co., NM |
| CHECK APPROPRIATE BOX(s |) TO INDICATE NATURE OF NOTICE, REPO | ORT, OR OTHER DATA |
| TYPE OF SUBMISSION | TYPE OF ACTION | |
| Notice of Intent | Abandonment | Change of Plans |
| | Recompletion | New Construction |
| Subsequent Report | Plugging Back | Non-Routine Fracturing |
| | Casing Repair | Water Shut-Off |
| Final Abandonment Notice | Altering Casing | Conversion to Injection |
| | Other Spud & set surface csg | Dispose Water |
| | | (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) |
| 3. Describe Proposed or Completed Operations (Clearly state all personnel proposed and transporting deaths for all produces | rtinent details, and give pertinent dates, including estimated date of starting any pro | |
| locations and measured and true vertical depths for all market | ACCEPTED FOR DECODE | |
| Spud well at 5:30 p.m., on 12/18/94 | The second secon | |
| Ran 8 5/8" csg as follows: Guide shoe @ 434' 2 jts 8 5/8", 24 ppf, J-55, 8rd | JAN 1 995 | em. |
| Float collar 347' 8 jts 8 5/8", 24 ppf, J-55, 8rd | | ्री है। 19 (19) (19) (19) 10) (19) (19) |
| Cemented csg as follows: | D 40 . 40 H / 1 D 40 . 40 . 5 | 60 (4) |
| | D-20 + 10 lbs/sk D-42 + 2% S-1 + 1/4 lb/sk D-29 | • |
| (Slurry weight = 12 | .7 lbs/gal Slurry yield = 1.94 cft/sk) | (1) |
| 200 sx C + 2% S-1 | | |
| (Slurry weight = 14.8 lbs/gal Slurry yield = 1.32 cft/sk) Circ'd 120 sx to surface. | | 0.17 20. |
| 4. I hereby certify that the foregoing is true and correct | KAREN ROSA ENGINEERING TECHNICIAN | Date 12/20/94 |
| igino - III | 1 inc | Date 14/40/74 |