

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):				38. GEOLOGIC MARKERS		
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	MEAS. DEPTH	TRUE VERT. DEPTH
Rustler	312	490	ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.. (continued from the front)			
Salado	490	1320				
Tansill	1320	1474				
Yates	1474	1770				
Seven Rivers	1770	2366				
Queen	2366	2780				
Grayburg	2780	3094				
San Andres	3094	4065 (TD)				
		DEPTH				
		3360'-3507'	Acidized w/1175 gals 15% HCl acid.			
		3133'-3261'	Acidized w/2150 gals 15% HCl acid.			
		3133'-3507'	Frac'd w/18,000 gals gel + 31,300# 20/40 Brady sand			
		2965'-3091'	Acidized w/1525 gals 15% HCl acid.			
		2800'-2926'	Acidized w/1000 gals 15% HCl acid.			
		2800'-3091'	Frac'd w/26,500 gals gel + 71,000# 20/40 Brady sand + 20,000# resin coated sand.			