

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

101
111
Alameda, N.M.

FORM APPROVED
Budget Bureau No. 1004-0135
Expires March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☐ Gas Well ☒ Other W I W

2. Name of Operator

DEVON ENERGY CORPORATION (NEVADA)

3. Address and Telephone No.

20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405) 235-3611

4. Location of Well (Footage. Sec., T., R., M., or Survey Description)

1989' FSL & 2001' FEL, Sec. 7-17S-31E

5. Lease Designation and Serial No.

LC-029435-A

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

J. L. Keel "A" #28

9. API Well No.

30-015-28231

10. Field and Pool, or Exploratory Area

Grayburg Jackson

11. County or Parish, State

Eddy County, NM

CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

☐ Abandonment

☐ Recompletion

☒ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Acidized

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well was plugged back and acidized as follows:

5/30/98 – RIH w/bit & scraper to 3619'. Set pkr @ 3485' and tested for communication.
Set CIBP @ 3485'.

6/1/98 – Acidized Jackson perfs 3365'-3452' w/750 gals 15% HCl acid + 500# rock salt.
Acidized Lovington perfs 3130'-3255' w/1500 gals 15% HCl acid + 3000# rock salt.
Acidized Grayburg perfs 2770'-3079' w/1800 gals 15% HCl acid + 3000# rock salt.

6/2/98 – Swabbed back. Set pkr @ 2698.60' and tested to 300 psi for 30 minutes.
Put well back on injection.

14. I hereby certify that the foregoing is true and correct

Signed Karen Byers
(This space for Federal or State office use)

Karen Byers

Title Engineering Technician

Date 6/5/98

Approved by _____
Conditions of approval, if any:

Title

ACCEPTED FOR RECORD

(ORIG. SGD.) DAVID R. GLASS

Date

JUN 17 1998

RECEIVED
JUN 10 1949

RECEIVED
JUN 10 1949

RECEIVED
JUN 10 1949