Form 3160-5 (June 1990)

pproved by

conditions of approval, if any:

UNITED STATES DEPARTMEN. JF THE INTERIOR BUREAU OF LAND MANAGEMENT

M	OIL	CONS	COMMISSIO
r	awer	DD	00210

Drawer DD Artesia, NM 88210 FORM APPROVED CIST

Budget Bureau No. 1004-0135 Expires March 31, 1993 SUNDRY NOTICES AND REPORTS ON WELLS 5. Lease Designation and Serial No. Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. LC-029435-B Use "APPLICATION FOR PERMIT—" for such proposals 6. If Indian, Allottee or Tribe Name SUBMIT IN TRIPLICATE 7. If Unit or CA, Agreement Designation 1. Type of Well ⊠ Oil Well ☐ Gas ☐ Other 8. Well Name and No. 2. Name of Operator **DEVON ENERGY OPERATING CORPORATION** J.L. KEEL "B" 90 3. Address and Telephone No. 9. API Well No. 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405) 235-3611 30-025-10. Field and Pool, or Exploratory Area 4. Location of Well (Footage. Sec., T., R., M., or Survey Description) 2575' FNL & 1335' FWL, SEC. 8-T17S-R31E GRAYBURG-JACKSON 11. County or Parish, State EDDY COUNTY, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Plans Recompletion **New Construction** Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Final Abandonment Notice Altering Casing Conversion to Injection Other Spud, TD'd & set surf prod csg. Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Spud well at 4:30 PM, 03/18/95. Ran 8 5/8" surface csg as follows: 11 jts 8 5/8" 24#, J-55, 8rd ST&C, 457.47'. Float shoe @ 475. Cemented csg as follows: Lead 125 sx Pacesetter Lite w/ 6% Gel + 2% CaCl2 + 1/4 #/sk Celloseal 200 sx Class C w/ 2% CaCl2 (weight 14.8 #/gal, yield 1.32 cf/sk). Circulated 60 sx cmt to surface. MAY 1 0 1995 Reach TD of 4155' at 1:30 PM 3/24/95. Ran 5½" production csg as follows: 87 jts 5½" 15.5#, J-55, 8rd LT&C, 3673.94'; 1 jt 5½" 15.5# 8r C 6 128. 10 1945. 5½" 15.5#, J-55, 8rd LT&C, 352.43'. Float shoe at 4054', float collar at 4015'. Cemented csg as follows: Lead 800 sx Pacesetter Lite w/ 4% Ataclay, 10% salt & 1/4 #/sk Celloseal (Weight 254 #/gal, yield 2.03 cf/sk). Tail w/ 350 sx Class C w/ 10% Thixad & 1/4 #/sk Celloseal (Weight 14.2 #/gal, yield 1.6 cf/sk). Circulated 83 sx cmt to surface. 111 4. I hereby certify that the foregoing is true and correct DIANA BOOHER ENGINEERING TECHNICIAN Title Date 04/20/95 This space for Federal or State office use)

itle 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to ny matter within its jurisdiction.

Date