Form 3160-5 (June 1990)

UNIT T STATES DEPARTMEN. JF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

NM OIL CONS COMME Drawer DD

	Artesia, NM Con-		
FORM APPROVED			
	Budget Bureau No. 1004-0135		
	Expires March 31, 1993		
I	5 Lease Designation and Serial No.		

SUNDRY NOTICES	5. Lease Designation and Serial No.		
Do not use this form for proposals to drill	LC-029435-B		
Use "APPLICATION Fo	6. If Indian, Allottee or Tribe Name		
SUBMIT	N/A		
1. Type of Well	7. If Unit or CA, Agreement Designation		
Type of Well	N/A		
2. Name of Operator	8. Well Name and No.		
DEVON ENERGY OPERATING CORPOR	1 1 14 1 1 1 PH 1107		
3. Address and Telephone No.	J. L. Keel "B" #87		
20 NORTH BROADWAY, SUITE 1500, OKLAHO	30-015-28249		
4. Location of Well (Footage, Sec., T., R., M., or Survey D	10. Field and Pool, or Exploratory Area		
40' FNL & 40' FEL, Sec. 8-17S-31E		Grayburg Jackson Q, SR, GB, SA	
		11. County or Parish, State	
		Eddy County, NM	
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA			
TYPE OF SUBMISSION TYPE OF ACTION			
Notice of Intent			
Notice of Intent	Abandonment Recompletion	Change of Plans	
Subsequent Report	Plugging Back	New Construction Non-Routine Fracturing	
	Casing Repair	Water Shut-Off	
Final Abandonment Notice	Altering Casing	Conversion to Injection	
	Other Spud, TD'd & set csg	Dispose Water	
		(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	
13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*			
Spud well on 8/20/95.			
Ran 8 5/8" surface csg as follows: 12 jts 8 5/8", 24#, J-55, 8rd ST&C, 499.18'. Csg shoe @ 513'.			
Cemented csg as follows: Lead w/180 sxs PSL "C" + 2% CaCl + 1/4 lb/sk cello-seal			
(wt. 12.8 lbs/gal, yield 1.86 cft/sk). Tail in w/200 sxs Characters			
14.8 lbs/gal, yield 1.32 cft/sk). Circ'd cement to surface			
Reached TD of 4275' on 8/27/95.			
Ran 5 1/2" surface csg as follows: top - 92 jts 5 1/2", 15.5#, J-55, 8rd LT&C, 39\$\vec{10}\$\vec{10}\$\vec{10}\$\vec{10}\$\vec{10}\$\vec{10}\$			
marker - 1 jt 5 1/2", 15.5#, J-55, 8rd LT&C, 29.53'			
	btm - 9 its 5 1/2", 15.5#, J-55, 8rd	LT& OHR SE ON DUN	
Cemented csg as follows: Lead w/1200 sxs PSL "C" + 5% salt + 4% gel + 14 lb/sk sello-seal			
	o lbs/sk Gil (wt. 12.9 lbs/gal, yield 1.88 cft/s)	k). Tail in w/300 sxs Class H +	
10	0% Gypsum + 1/4 lbs/sk cello-seal (wt 14.5 li	bs/sk, vield 1.52 cft/sk). Circ'd	
C€	ement to surface.	, ,	
14. I heraby certify that the formal in the first that the			
14. I hereby certify that the foregoing is true and correct KAREN BYERS			
Signed Karen Buons	Title ENGINEERING TECHNICIAN	Date 9/8/95	
(This space for Federal or State office use)		Date 2002	
Agreemed by			
Approved byConditions of approval, if any:	Title	Date	