Form 3160-5 (June 1990)

UNIT STATES DEPARTMEN. JF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

NM OIL CONS COMMIS Drawer DD Art SARM APPNOVED 210 Budget Bureau No. 1004-0135 Expires March 31, 1993	
ease Designation and Serial No.	
000425 4	[

	LAND MANAGEMENT	Art FORM APPMOVED 10
Do not use this form for proposals to drill	S AND REPORTS ON WELLS or to deepen or reentry to a different reservoir. OR PERMIT—" for such proposals	5. Lease Designation and Serial No. LC 029435-A 6. If Indian, Allottee or Tribe Name
	IN TRIPLICATE	NA
1. Type of Well Signature Gas Well Well Other		7. If Unit or CA, Agreement Designation NA
2. Name of Operator		8. Well Name and No.
DEVON ENERGY OPERATING CORPORA	ATION	J.L. Keel A #33
 Address and Telephone No. NORTH BROADWAY, SUITE 1500, OK 	LAHOMA CITY, OKLAHOMA 73102 (405) 235-3611	9. API Well No. 30-015-28262
4. Location of Well (Footage. Sec., T., R., M., or Survey Description)		10. Field and Pool, or Exploratory Area
2593' FNL & 1310' FEL, Sec. 7-T17S-R31E		GRAYBURG-JACKSON
	Unit H	11. County or Parish, State
		EDDY COUNTY, NEW MEXICO
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REP	PORT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent	Abandonment	Change of Plans
Mar.	Recompletion	New Construction
Subsequent Report	Plugging Back	Non-Routine Fracturing
Final Abandonment Notice	Casing Repair Altering Casing	Water Shut-Off
	Other Spud, TD'd & Set surf prod csg.	Conversion to Injection Dispose Water
		(Note: Report results of multiple completion on Well
 Describe Proposed or Completed Operations (Clearly state all per locations and measured and true vertical depths for all market 	tinent details, and give pertinent dates, including estimated date of starting any ps and zones pertinent to this work.)*	proposed work. If well is directionally drilled, give subsurface
Spud well at 4:15 PM, 04/02/95.		
Ran 8 5/8" surface csg as follows: 10	jts 8 5/8" 24#, J-55, 8rd ST&C, 416'. Float s	shoe at 434' plug @ 334'
Tail w/ 200 sx C + 2% CaCl2. (sx 35/65 Lite "C" + 6% Gel + 2% CaCl2. (Veight 14.8 #/gal, yield 1.32 cf/sk).	Weight 12.7 #/gal, yield 1.93 cf/sk).
Circulated 105 sx cmt to surface.	<u></u> ,	
Jis 372 13.3#, J-33, 8rd L1&C, Cemented csg as follows: 600 sx 35/6	33 jts 5½" 15.5#, J-55, 8rd LT&C, 3623'; 1 jt 382'. Float shoe @ 4009', Float collar @ 396 5 Lite Poz C + 4% Ataclay + ¼ #/sk Cellosea iixad (H) + ¼ #/sk Celloseal. (Weight 14.2 #/	3/ \// (Weight 12.5 #/gal, yield. 2.03 //gal, yield 1.6 cf/sk.)
	ONL CO	A. Diw
4. I hereby certify that the foregoing is true and correct	DIANA BOOHER DIST	2
igned Diana Booher	Title ENGINEERING TECHNICIAN	Date 05/18/95
This space for Federal or State office use pproved by onditions of approval, if any	Title	Date
onomion of approval, it any:		