Form 3160-5 (June 1990)

UNIT) STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

NM OIL CONS COMMISSION I wer DD Artesia, NM 88210



FORM APPROVED

		Budget Bureau No. 1004-0135 Expires March 31, 1993	
SUNDRY N	OTICES AND REPORTS ON WELLS	5. Lease Designation and Serial No.	
aconot use this form for proposals	OTICES AND REPORTS ON WELLS to drill or to deepen or reentry to a different reservoir.	LC-029435-B	
Use "APPLICAT	TION FOR PERMIT—" for such proposals	6. If Indian, Allottee or Tribe Name	
, , , , , , , , , , , , , , , , , , , ,	SUBMIT IN TRIPLICATE	N/A	
1/3		7. If Unit or CA, Agreement Designation	
Gas Other			
Well Other		N/A 8. Well Name and No.	
DEVON ENERGY OPERATING	CORPORATION	6. Well Marile and No.	
3. Address and Telephone No.		J. L. Keel "B" #70	
20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405)552-4527 4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		9. API Well No.	
		30-015-28290	
		10. Field and Pool, or Exploratory Area	
1338' FNL & 40' FEL, Sec. 5-17S-31E		Grayburg Jackson Q, SR, GB, SA 11. County or Parish, State	
		Eddy County, NM	
CHECK ADDDODDIATE	POV(a) TO INDICATE MATURE OF MOTION OF	TOORT OR OTHER DATE:	
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA			
TYPE OF SUBMISSION	TYPE OF ACTIO	TYPE OF ACTION	
Notice of Intent	Abandonment	Change of Plans	
∑ 1	Recompletion	New Construction	
∑] Subsequent Report	Plugging Back	Non-Routine Fracturing	
	Casing Repair	Water Shut-Off	
Final Abandonment Notice	Altering Casing	Conversion to Injection	
	Other Spud, TD'd & set csg	Dispose Water	
	state all pertinent details, and give pertinent dates, including estimated date of starting ar	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	
Spud well @ 1:30 p.m., Ran 8 5/8" surfa Cemente	, 9/21/95. ace csg as follows: 13 jts 8 5/8", 24# J-55, 8rd \$Toda csg as follows: 180 sxs PSL "C" + 6% gel + 2% t 12.9 lbs/gal, yield 1.86 cft/sk. Tailed in w/200 sxs s/gal, yield 1.41 cft/sk. Circ'd cmt to surface.	CaCl + 1/4 lb/sk cello-seal.	
co Cemente lbs	-	10% Gypsum + 1/4 lb/sk cello-seal.	
4. Thombus and Gustavalla C			
4. I hereby certify that the foregoing is true and	correct KAREN BYERS		
igned Karlin Dyl	Title ENGINEERING TECHNICIAN	Date 10.6/95	
It is space for Federal or State office use)			
improved by			
approved by	Title	Date	
		J. Tark	