Form 3160-5 (June 1990)

UNITY STATES DEPARTMEN. OF THE INTERIOR BUREAU OF LAND MANAGEMENT



FORM APPROVED

BUREAU OF LAND MANAGEMENT

	nt.EN	Expires March 31, 1993
SUNDRY NOTICES	S AND REPORTS ON WELLS	5. Lease Designation and Serial No.
	or to deepen or reentry to a different reservoir	r. LC-029426-B
Use "APPLICATION FO		If Indian, Allottee or Tribe Name
		J3
SUBMIT	TIN TRIPLICATE CARC	N/A
1. Type of Well	An	7. If Unit or CA, Agreement Designation
⊠ÍOil ∏ Gas ∏ ottor		N/A
2. Name of Operator		8. Well Name and No.
DEVON ENERGY OPERATING CORPOR	ATION	
		H. E. West "B" #80
3. Address and Telephone No.		9. API Well No.
20 NORTH BROADWAY, SUITE 1500, OKLAHO	DMA CITY, OKLAHOMA 73102 (405)552-4527	30-015-28299
4. Location of Well (Footage. Sec., T., R., M., or Survey Description)		10. Field and Pool, or Exploratory Area
1410' FSL & 193' FWL, Unit L, Sec. 9-17S-31E		Grayburg Jackson Q, SR, GB, SA
,		11. County or Parish, State
		Eddy County, NM
OUTOK ADDDODDIATE DOM) TO MOIO TE	
CHECK APPROPRIATE BOX(s	s) TO INDICATE NATURE OF NOTICE, F	REPORT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACT	TON
Notice of Intent	□ A14	
Notice of file.it	Abandonment	Change of Plans
Subsequent Report	Recompletion Plugging Back	New Construction
5 Subsequent Report		Non-Routine Fracturing
Final Abandonment Notice	Casing Repair Altering Casing	Water Shut-Off
I mai Abandoninent Honec	Other Spud, TD'd & set csg	Conversion to Injection
	Other Spud, 1D d & set csg	Dispose Water (Note: Report results of multiple completion on Well
12 Describe Proposed of Completed Complete (Clarks day 1)		Completion or Recompletion Report and Log form)
locations and measured and true vertical depths for all market	ertinent details, and give pertinent dates, including estimated date of startings and zones pertinent to this work.)*	g any proposed work. If well is directionally drilled, give subsurfac
	,	
C 1 11 11/07/07		
Spud well on 11/25/95.		
Ran 8 5/8" surface csg	as follows: 13 jts 8 5/8", 24#, J-55, 8rd S	ST&C. Csg shoe @ 539'.
Cemented csg as follow	vs: Lead w/180 sx 35/65 POZ "C" + 6	de 2 15 10 17 174 that celloseal wit
12.7 npg vield 1	.86 cft/sk. Tailed in w/200 sx Class "OFF	· Sell 132
cft/sk. Circ'd c		3270 Sait, Wt 14.0 ppg, yield 1.32
CIUSK. CITC U C	ait to surface.	1211 6 5 6230
· ·		JAN 2 6 1983
Reached TD of 4305' on 11/30		
Ran 5 1/2" production	csg as follows: 100 jts 5 1/2", 15.50#(0)	BL 8fd CT&C Float/shoe @ 4304'
float collar 4257	'. Top - 90 jts, 3926', middle - 1 jt, 20', b	ottom 201'
Camentad ass as fallow	wee I and w/675 or 25/65 DOZ "O" + 40/	
Cemented esg as follow	ys: Lead w/675 sx 35/65 POZ "C" + 4% g	gel + 5% sait + 1/4 lb/sk celloseal, wt
13 ppg, yield 1.7	6 cft/sk. Tailed in w/300 sx Class "H" + 1	0% Gypsum + 1/4 lb/sk celloseal, wt
14.5 ppg, yield 1	.52 cft/sk. Top of cement per CBL 802'.	•
	-	
14. I hereby certify that the foregoing is true and correct		
	KAREN BYERS	
Signed Karly Supra	Title ENGINEERING TECHNICIAN	Date 12/14/95
(This space for Federal or State office use)		
7		
Approved by	Title	Date
Conditions of approval, if any:		

८७८

JAN 2 4