Form 3160-5 (June 1990)

UNITED STATES DEPARTMEN. JF THE INTERIOR BUREAU OF LAND MANAGEMENT

NM OIL CONS COMMON OF THE PROPERTY OF THE PROP

CISP

BUREAU OF LAND MANAGEMENT FORM APPROVED Budget Bureau No. 1004-0135 Expires March 31, 1993 5. Lease Designation and Serial No. SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. LC-029435-A Use "APPLICATION FOR PERMIT—" for such proposals 6. If Indian, Allottee or Tribe Name SUBMIT IN TRIPLICATE 7. If Unit or CA, Agreement Designation 1. Type of Well Oil Well ☐ Gas Wel Other 8. Well Name and No. 2. Name of Operator **DEVON ENERGY OPERATING CORPORATION** J. L. Keel "A" #30 3. Address and Telephone No. 9. API Well No. 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73 102 (405)552-4527 30-015-28306 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 430' FSL & 2013' FEL, Sec. 7-17S-31E Grayburg Jackson Q, SR, GB, SA 11. County or Parish, State Eddy County, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Plans Recompletion New Construction Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Final Abandonment Notice Altering Casing Conversion to Injection Other Spud, TD'd & set csg Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Spud well on 8/21/95. Ran 13 3/8" csg as follows: 11 jts, 13 3/8", 48#, H-40, ST&C, 465.20'. Csg shoe @ 459'. Cemented csg as follows: 500 sxs PSL "C" + 6% gel + 2% salt + 1/4 lb/sk cello-seal + 10 lbs/sk Gil (wt 12.7 lbs/gal, yield 1.90 cft/sk). Tail in w/200 sxs Class "C" + 2% CaCl (wt 14.8 lbs/gal, yield 1.32 cft/sk). Circ'd cement Reached TD of 3765' on 8/29/95. Ran 5 1/2" csg as follows: top - 78 jts 5 1/2", 15.5#, J-55, 8rd LT&C, 3364.77" marker - 1 jt 5 1/2", 15.5#, J-55, 8rd LT&C, 15.89' btm - 9 jts 5 1/2", 15.5#, J-55, 8rd LT&C, 390.17 Cemented csg as follows: 625 sxs PSL "C" + 4% gel + 5% salt + 1/470 se caracteristics. lbs/gal, yield 1.56 cft/sk). Tail in w/250 sxs Class "H" + 10% gyp + 1/4 lb/sk cello-seal (wt 14.5 lbs/gal, yield 1.52 cft/sk). Circ'd cement to surface.

I hereby certify that the foregoing is true and correct ned Hann Bylns	KAREN BYERS ENGINEERING TECHN	IICIAN Date 9/8/95
nis space for Federal or State office usa		FACAFPIED FOR READEL
Approved byConditions of approval, if any:	Title	Date farm

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.