

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE

NM 011 DD FORM APPROVED
Dr 18, NM 88210
(Sealing and instructions on reverse side)

clsr

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL:		OIL WELL ☒	GAS WELL ☐	DRY ☐	Other ☐		
b. TYPE OF COMPLETION:		NEW WELL ☒	WORK OVER ☐	DEEP-EN ☐	PLUG BACK ☐	DIFF RESERV ☐	Other ☐
2. NAME OF OPERATOR DEVON ENERGY OPERATING CORPORATION							
3. ADDRESS AND TELEPHONE NO. 20 N. BROADWAY, SUITE 1500, OKC, OK 73102-8260 (405) 235-3611							
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)* At surface 2622' FNL & 1330' FEL At top prod. interval reported below (SAME) At total depth (SAME)							

5. LEASE DESIGNATION AND SERIAL NO. LC-029426-A
6. IF INDIAN, ALLOTTEE OR TRIBE NAME N/A
7. UNIT AGREEMENT NAME N/A
8. FARM OR LEASE NAME, WELL NO. H. E. West "A" #32
9. API WELL NO. 30-015-28324
10. FIELD AND POOL, OR WILDCAT Grayburg Jackson (Q, SR, GB, SA)
11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA Sec. 3-17S-31E

14. PERMIT NO.		DATE ISSUED		12. COUNTY OR PARISH Eddy County,	13. STATE NM	
15. DATE SPUDDED 2/23/95	16. DATE T.D. REACHED 3/1/95	17. DATE COMPL. (Ready to prod.) 5/10/95	18. ELEVATIONS (DF, RKB, RT, GR, ETC.)* 3964' GR		19. ELEV. CASINGHEAD 3964'	
20. TOTAL DEPTH, MD & TVD 4425'	21. PLUG, BACK T.D., MD & TVD 4376'	22. IF MULTIPLE COMPL., HOW MANY* No		23. INTERVALS DRILLED BY →	24. ROTARY TOOLS X	25. CABLE TOOLS
24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)* Slaughter 4168'-4202', Vacuum, Lovington, Middle & Lower Jackson 3672'-3113', Premier 3553'-3587', Grayburg 3348'-3524'						25. WAS DIRECTIONAL SURVEY MADE Yes
26. TYPE ELECTRIC AND OTHER LOGS RUN DLL/MLL/GR/X-Y Cal, ZDL/CN/GR/X-Y Cal, CEL						27. WAS WELL CORED No

28. CASING RECORD (Report all strings set in well)						
CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, FEET BELOW HOLE	AMOUNT CEMENT, CUBIC FEET	REMARKS
8 5/8" J-55	24	632'	12 1/4"	Surf, 130 sxs POZ/C Lite	None	
				+ 200 sxs Class "C"		
5 1/2" J-55	15.5	4424'	7 7/8"	Surf, 600 sxs POZ/C Lite	None	
				+ 375 sxs RFC		

29. LINER RECORD					30. OIL TUBING RECORD		
SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2 7/8"	4287.50	None

31. PERFORATION RECORD (Interval, size and number) Slaughter 4168'-4202' (9-.40" holes) Vacuum, Lovington, Middle & Lower Jackson 3672'-3113' (21-.40" holes) Premier 3553'-3587' (7-.40" holes) Grayburg 3348'-3524' (15-.40" holes)	32. ACID SHOT, FRACTURE, CEMENT SQUEEZE, ETC. <table border="1"><tr><th>DEPTH INTERVAL (MD)</th><th>AMOUNT AND KIND OF MATERIAL USED</th></tr><tr><td>4168'-4202'</td><td>Acidized w/975 gals 15% HCl acid.</td></tr><tr><td>3861'-4113'</td><td>Acidized w/2250 gals 15% HCl acid.</td></tr><tr><td>3672'-3758'</td><td>Acidized w/1600 gals 15% HCl acid.</td></tr><tr><td>3672'-4113'</td><td>Frac'd w/22,000 gals gel + 56,000# 20/40 Brady sand +</td></tr></table>	DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED	4168'-4202'	Acidized w/975 gals 15% HCl acid.	3861'-4113'	Acidized w/2250 gals 15% HCl acid.	3672'-3758'	Acidized w/1600 gals 15% HCl acid.	3672'-4113'	Frac'd w/22,000 gals gel + 56,000# 20/40 Brady sand +
DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED										
4168'-4202'	Acidized w/975 gals 15% HCl acid.										
3861'-4113'	Acidized w/2250 gals 15% HCl acid.										
3672'-3758'	Acidized w/1600 gals 15% HCl acid.										
3672'-4113'	Frac'd w/22,000 gals gel + 56,000# 20/40 Brady sand +										

33.* PRODUCTION							
DATE FIRST PRODUCTION 5/13/95		PRODUCTIONS METHOD I (Flowing, gas lift, pumping—size and type of pump) Pumping 2 1/2" x 2" x 16' RSTC pump				WELL STATUS (Producing or shut-in) Producing	
DATE OF TEST 5/14/95	HOURS TESTED 24	CHOKE SIZE N/A	PROD'N FOR TEST PERIOD →	OIL-BBL. 40	GAS-MCF. 0	WATER-BBL. 189	GAS-OIL RATIO N/A
FLOW. TUBING PRESS. N/A	CASING PRESSURE 40	CALCULATED 24-HOUR RATE →	OIL-BBL. 40	GAS-MCF. 0	WATER-BBL. 189	OIL GRAVITY-API (CORR.) 37	

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) Sold	TEST WITNESSED BY Richard Frazee
--	-------------------------------------

35. LIST OF ATTACHMENTS Deviation Survey & Logs
--

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED Karen Rosa ByersKAREN ROSA BYERS
TITLE ENGINEERING TECHNICIANDATE 6/23/95

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.