Form 3160-5 (June 1990)

Conditions of approval, if any:

any matter within its jurisdiction.

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to ark departs

## UNIT STATES DEPARTMEN'. JF THE INTERIOR BUREAU OF LAND MANAGEMENT

NM OIL CONS COMMISSION

Drawer DD

Artesform APPROVED

any false, fictitious or fraudulent statements or representations as to

Budget Bureau No. 1004-0135 Expires March 31, 1993

Do not use this form for proposals to drill	S AND REPORTS ON WELLS or to deepen or reentry to a different reservoir. OR PERMIT—" for such proposals	5. Lease Designation and Serial No.  LC 029435-B  6. If Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE		NA
1. Type of Well  ☑ Oil ☐ Gas ☐ Other  Well ☐ Other		7. If Unit or CA, Agreement Designation NA
2. Name of Operator DEVON ENERGY OPERATING CORPORA	ATION	8. Well Name and No.
3. Address and Telephone No. 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405) 235-3611		J.L. KEEL "B" #86  9. API Well No.  30-015-28484
4. Location of Well (Footage. Sec., T., R., M., or Survey Description)		10. Field and Pool, or Exploratory Area
49' FSL & 2520' FWL, SEC. 5-17S-31E		GRAYBURG-JACKSON 11. County or Parish, State
		EDDY COUNTY, NEW MEXICO
CHECK APPROPRIATE BOX(s	) TO INDICATE NATURE OF NOTICE, REP	ORT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
<ul> <li>Notice of Intent</li> <li>Subsequent Report</li> <li>Final Abandonment Notice</li> </ul>	Abandonment Recompletion Plugging Back Casing Repair	Change of Plans  New Construction  Non-Routine Fracturing  Water Shut-Off
	Altering Casing  Other Spud, TD;d & set surf prod csg.  Tinent details, and give pertinent dates, including estimated date of starting any participant to this work.	Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
Spud well @ 4:00 PM, 5/23/95. Ran 8 5/8" surface csg as follows: 10 jts Cemented csg as follows: Lead w/150 sx	8 5/8" 24#, J-55, 8rd ST&C, 418'. Float those at PSL "C" + 2% CaCl2. (Weight 12.7 #/gal, yield	MENTED - 1
5/2 15.5#, J-55, 8rd L1&C, 438'.  Cemented csg as follows: 1250 sx PSL "C	s 5½" 15.5#, J-55, 8rd LT&C, 3752'; 1 jt 5½" 15 Float shoe @ 4168', Float collar @ 4140'. C" + 4% Ataclay + 10% Salt +½ #/sk Celloseal. ('a.') L') Tail in w/ 350 sx H + 10% thixad + ½ #/sk Ce	The first 500 sy have 5 #/ck ail)
Circulated 173 sx cmt to surface.		
14. I hereby certify that the foregoing is true and correct Signed Diamo Booker  (This of Fall 1)	DIANA BOOHER  Title ENGINEERING TECHNICIAN	Date 06/01/95
(This space for Federal or State office use)  Approved by	Title	