Form 3160-5 (June 1990)

Conditions of approval, if any

UNIT > STATES DEPARTMEN. OF THE INTERIOR

Cl	ς	F
----	---	---

OIL CONSERVATION DIV BUREAU OF LAND MANAGEMENT 811 S. 1st ST. Budget Bureau No. 1004-0135 5. Lease Designation and Serial No. SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. LC-029426-B Use "APPLICATION FOR PERMIT—" for such proposals 6. If Indian, Allottee or Tribe Name SUBMIT IN TRIPLICATE 7. If Unit or CA, Agreement Designation 1. Type of Well ⊠ Oil Well ☐ Other 8. Well Name and No. 2. Name of Operator **DEVON ENERGY OPERATING CORPORATION** H. E. West "B" #88 9. API Well No. 3. Address and Telephone No. 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405)552-4527 30-015-28537 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage. Sec., T., R., M., or Survey Description) Grayburg Jackson Q, SR, GB, SA 1309'FNL & 1310' FWL, Unit D, Sec. 9-17S-31E 11. County or Parish, State Eddy County, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION TYPE OF SUBMISSION Abandonment Change of Plans Notice of Intent New Construction Recompletion Non-Routine Fracturing Subsequent Report Plugging Back Water Shut-Off Casing Repair Conversion to Injection Final Abandonment Notice Altering Casing Other Spud, TD'd & set csg Dispose Water (Note: Report results of multiple comple ompletion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Spud well on 11/10/95. Ran 8 5/8" surface csg as follows: 13 jts 8 5/8", 24# J-55, 8rd ST&C, 534.45'. Csg shoe @ 551'. Cemented csg as follows: Lead - 180 sx 35/65 POZ "C" + 6% gel + 2% CaCl₂ + 1/4 lb/sk Celloseal, wt 12.7 ppg, yield 1.93 cft/sk. Tail - 200 sx Class "C" Tail - 200 sx Class "C" Circ'd cmt to surface. JAN 2 2 1996 Reached TD of 4345' on 11/16/95. Ran 5 1/2" prod csg as follows: 101 jts 5 1/2", 15.50# J-55, and LT&C. top 01 jts, 3964.82'; middle - 1 jt, 14.35'; and bottom - 9 jts, 396.86'. Csg showed 4344; Walt collar 4297'. Cemented csg as follows: Lead - 1565 sx 35/65 POZ "C" + 4% go #\$5% alt + 1/4 lb/sk Celloseal. Tail - 380 sx Class "H: + 10% Thixad + 1/4 lb/sk Celloseal, wt 14.5 ppg, yield 1.52 cft/sk. Circ'd cmt to surface. 14. I hereby certify that the foregoing is true and correct KAREN BYERS ENGINEERING TECHNICIAN Date 11/29/95 Title (This space for Federal or Sta Approved by

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.