

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):				38. GEOLOGIC MARKERS		
FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	MEAS. DEPTH	TRUE VERT. DEPTH
Rustler	370	590	ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.. (continued from the front)			
Salado	590	1435				
Tansill	1435	1594				
Yates	1594	1897				
Seven Rivers	1897	2518				
Queen	2518	2940				
Grayburg	2940	3232				
San Andres	3232	4160 (TD)				
		DEPTH				
		3685'-3718'				
		3505'-3636'	Acidized w/750 gals 15% HCl acid.			
			Acidized w/1150 gals 15% HCl acid.			
		3505'-3718'	Frac'd w/20,000 gals gel + 55,000# 20/40 Brady sand + 12,000# 20/40 SLC resin coated sand.			
		3278'-3394'	Acidized w/1000 gals 15% HCl acid.			
		2994'-3230'	Acidized w/1500 gals 15% HCl acid.			
		2994'-3394'	Frac'd w/44,000 gals gel + 141,000# 20/40 Brady sand + 24,000# 16/30 SLC resin coated sand.			