Form 3160-5 UNI	י STATES	
(June 1990) DEPARTMEN	NI OF THE INTERIOR	ح\ک
BUREAU OF I	LAND MANAGEMENT	FORM APPROVED Budget Bureau No. 1004-0135 Expires March 31, 1993
SUNDRY NOTICES	5. Lease Designation and Serial No.	
Do not use this form for proposals to drill o	LC-029395-A	
Use "APPLICATION FO	6. If Indian, Allottee or Tribe Name	
SUBMIT IN TRIPLICATE		N/A
1. T		7. If Unit or CA, Agreement Designation
I. Type of Well ⊠ Oii □ Gas □ Other Well Well		N/A
2. Name of Operator		8. Well Name and No.
DEVON ENERGY OPERATING CORPORA	Turner "A" #53	
Address and Telephone No.	9. API Well No.	
20 NORTH BROADWAY, SUITE 1500, OKLAHO	30-015-28773	
Location of Well (Footage. Sec., T., R., M., or Survey D	10. Field and Pool, or Exploratory Area	
2630' FSL & 1620' FEL, Sec. 18-17S-31E	Grayburg Jackson Q, SR, GB, SA	
		11. County or Parish, State
		Eddy County, NM
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REF	PORT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent	Abandonment	Change of Plans

Recompletion

Plugging Back

Casing Repair

Altering Casing

Other Spud, TD'd & set csg

UNIT STATES

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estim	ated date of starting any proposed work. If well is directionally dilled, give subsurface
locations and measured and true vertical depths for all markers and zones pertinent to this work.)*	
Spud well @ 8:45 a.m., 2/8/96. Ran 8 5/8" surf csg as follows: 9 jts 8 5/8", 24#, J-55,	BECEMER
Spuu wen @ 0.45 a.m., 2/0/90.	
Ran 8 5/8" surf csg as follows: 9 its 8 5/8" 24# 1-55	8rd ST&C 35757' Csg shoe @ 57
Cemented csg as follows: Lead - 300 sx 65/35 POZ "	C'' + 6% gel + 1/4 lb/sk celloseabt 2% CaCl
	APR 1 1990
Cemented csg as follows: Lead - 300 sx 65/35 POZ "((wt 12.7 ppg, yield 1.86 cft/sk). Tailed in w/200	J sx Class "C" + 2% CaCl ₂ , (wf I4.8 ppg,

New Construction

Water Shut-Off

Dispose Water

Non-Routine Fracturing

Conversion to Injection

OIL CON. DIV. DIST. 2

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

yield 1.32 cft/sk). Circ'd cmt to surface.

Reached TD of 3780' on 2/13/96.

Subsequent Report

Final Abandonment Notice

Ran 5 1/2" production csg as follows: 87 jts 5 1/2", 15.50#, J-55, 8rd LT&C. Csg shoe @ 3779', float collar @ 3733'. Top - 77 jts, 3371.14', middle - 1 jt, 18.12', bottom - 9 jts, 396.48'. Cemented csg as follows: Lead - 625 sx 35/65 POZ "C" + 4% gel + 5% salt + 1/4 lb/sk celloseal, (wt 13 ppg, yield 1.76 cft/sk). Tailed in w/300 sx Cl "H" + 10% gypsum + 1/4 lb/sk celloseal, (wt 14.5 ppg, yield 1.52 cft/sk). Circ'd cmt to surface.

14. I hereby certify that the foregoing is true and correct Signed Kanen Bulno		EN BYERS NEERING TECHNICIAN Date 2/16/96
(This space for Federal or State office use)	<u> </u>	
Approved by Conditions of approval, if any:	Title	Date
		A anos
Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfull any matter within its jurisdiction.	y to make to any departm	ment or agency of the United States any false, fictitious of fraudulent statements or representations, as to