

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTSUBMIT IN DUPLICATE *
N.M. Oil Cons. Div.
811 S. 1st Street
Artesia, NM 88210-2834
Instructions (Reverse side)FORM APPROVED
OMB NO. 1004-0137
Expires February 28, 1995

c/sf

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

1a. TYPE OF WELL: OIL WELL ☒ GAS WELL ☐ DRY ☐ Other ☐				5. LEASE DESIGNATION AND SERIAL NO. L-029420-B	
b. TYPE OF COMPLETION: NEW ☐ WORK ☐ DEEP- ☐ PLUG ☐ DIFF. ☐ WELL ☒ OVER ☐ EN ☐ BACK ☐ RESVR. ☐ Other ☐				6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
2. Name of Operator The Wiser Oil Company (22922) ✓				7. UNIT AGREEMENT NAME Skelly Unit (17540)	
3. ADDRESS AND TELEPHONE NO. 8115 Preston Road Suite 400, Dallas, TX 75225 (214) 265-0080				8. FARM OR LEASE NAME, WELL NO. 262	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements) At Surface 105' FSL, 125' FEL, Unit P At top prod. Interval reported below At total depth				9. API WELL NO. 30-015-28789	
14. PERMIT NO. ☐ DATE ISSUED ☐				10. FIELD AND POOL, OR WILDCAT Grayburg Jackson QN GB SA (28509)	
15. DATE SPUDDED 2-13-96				11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA Sec. 21, 17S-31E, N.M.P.M	
16. DATE T.D. REACHED 2-20-96				12. COUNTY OR PARISH Eddy	
17. DATE COMPLETION (Ready To prod) 7-2-96				13. STATE NM	
18. ELEVATIONS (DF, RKB, RT, GR, ETC.) * 3806' GR				19. ELEV. CASINGHEAD	
20. TOTAL DEPTH, MD & TVD 3950'		21. PLUG BACK T.D., MD & TVD 3857'		22. IF MULTIPLE COMPL., HOW MANY *	
23. INTERVALS DRILLED BY → All				24. WAS WELL CORED No	
24. PRODUCING INTERVAL(S), OF THIS COMPLETION - TOP, BOTTOM, NAME (MD AND TVD) * 3401' - 3613' Grayburg & San Andres				25. WAS DIRECTIONAL SURVEY MADE Yes	
26. TYPE ELECTRIC AND OTHER LOGS RUN Dual Spaced Neutron & Cement Bond				27. WAS WELL CORED No	
28. CASING RECORD (Report all strings set in well)					
CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
8 5/8"	23#	491'	12 1/4"	325 sx Class C/2% CaCl2 & 1/4# Flocele/sk	Circ 76 sx
5 1/2"	17#	3950'	7 7/8"	1050 sx Hal Lite & 550 sx Class C/5%	Circ 114 sx
				Halad 334 & 3# KCL/sk	
29. LINER RECORD			30. TUBING RECORD		
SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT *	SCREEN (MD)	PACKER SET (MD)
				2 7/8"	3361'
31. PERFORATION RECORD (Interval, size and number) 3592-95, 96, 97, 98, 3603, 11, 12, 13 (9 holes) 3401, 02, 23, 24, 27, 28, 43, 47, 48, 58, 68, 69, 70, 73, 94, 95, 96, 3510, 20, 25 34, 37 (22 holes)			32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC. DEPTH INTERVAL (MD) AMOUNT AND KIND OF MATERIAL USED 3592-3613' Acidize/1300 gal 15% NEFE Acid 3592-3613' Acidize/1400 gal 15% NEFE Acid 3401-3537' Acidize/3300 gal 15% NEFE Acid 3401-3537' Frac/100,000# 16/30 sand + 40,000 gal Boragel +		
33. * PRODUCTION DATE FIRST PRODUCTION 7-2-96 PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) 2 1/2" x 1 1/2" x 20' Pump WELL STATUS (Producing or shut-in) Producing			12,000 gal gelled water		
DATE OF TEST 7-7-96	HOURS TESTED 24	CHOKE SIZE	PROD'N. FOR TEST PERIOD → 165	OIL—BBL. 81	GAS—MCF. 0
FLOW TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE → 165	OIL—BBL. 81	GAS—MCF. 0	WATER—BBL. 0
34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) Sold					TEST WITNESSED BY
35. LIST OF ATTACHMENTS Deviation Survey and Logs					
36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records. SIGNED <u>Michael R. Burch, CPL</u> TITLE <u>Agent for The Wiser Oil Company</u> DATE <u>9-13-96</u>					

*(See Instructions and Spaces for Additional Data on Reverse Side)

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	GEOLOGIC MARKERS	
					MEAS. DEPTH	TRUE VERT. DEPTH
0		430	430' Caliche & Red Beds	Anhy	430	
430		573	143' Anhydrite	Top Salt	573	
573		1578	1005' Salt	Base Salt	1578	
1578		3887	2309' Dolomite, Sand, Anhydrite	Yates	1764	
				7 Rivers	2045	
				Queen	2710	
				Grayburg	3124	
				San Andres	3547	