

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

OIL CONSERVATION DIV.  
CORRECTED  
MAY 1 1996  
BOSTON, MA 02111-2234

c/SF

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well  
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator  
DEVON ENERGY OPERATING CORPORATION

3. Address and Telephone No.  
20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405) 552-4527

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)  
1191' FSL & 1056' FEL, Sec. 18-17S-31E

5. Lease Designation and Serial No.  
LC-029395-A

6. If Indian, Allottee or Tribe Name  
N/A

7. If Unit or C.A. Agreement Designation  
N/A

8. Well Name and No.  
Turner "A" #40

9. API Well No.  
30-015-28792

10. Field and Pool, or Exploratory Area  
Grayburg Jackson Q, SR, GB, SA

11. County or Parish, State  
Eddy County, NM

CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION	
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment	<input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion	<input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Plugging Back	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> Water Shut-Off
	<input type="checkbox"/> Altering Casing	<input type="checkbox"/> Conversion to Injection
	<input checked="" type="checkbox"/> Other Spud, TD'd & set csg	<input type="checkbox"/> Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spud well @ 9:30 a.m., 3/5/96.

Ran 8 5/8" surface csg as follows: 10 jts 8 5/8", 24#, J-55, 8rd ST&C, 404.56'. Csg shoe @ 420'.

Cemented csg as follows: Lead - 300 sx 35/65 POZ "C" + 6% gel + 2% CaCl<sub>2</sub> + 1/4 lb/sk celloflake + 5 lbs/sk Gilsonite, (wt 12.7 ppg, yield 1.86 cft/sk). Tail - 200 sx Class "C" + 2% CaCl<sub>2</sub>, (wt 14.8 ppg, 1.32 cft/sk). Topped off via 1" tbg w/85 sx Cl "C". Circ'd cmt to surface.

Reached TD of 3810' on 3/12/96.

Ran 5 1/2" prod csg as follows: 92 jts 5 1/2", 15.50#, J-55, 8rd LT&C, 3426.86'. Csg shoe @ 3809', float collar @ 3763'.

Cemented csg as follows: Lead - 1000 sx PSL "C" + 4% gel + 5% salt + 1/4 lb/sk celloflake, (wt 13 ppg, yield 1.76 cft/sk). Tail - 300 sx Class "H" + 10% Gypsum + 1/4 lb/sk celloflake, (wt 14.5 ppg, yield 1.52 cft/sk). TOC @ 150'.

14. I hereby certify that the foregoing is true and correct

Signed Karen Byers  
(This space for Federal or State office use)

KAREN BYERS  
ENGINEERING TECHNICIAN

Date 4/26/96

Approved by  
Conditions of approval, if any:

Title

Date