Form 3160-5 (June 1990)) STATES			λ
		AND MANAGEN		RECEIVED	FORM APPROVED Budget Bureau No. 1004-0135
Do ກວt use this form Use	SUNDRY NOTICES for proposals to drill c #APPLICATION FO	r to deepen or reent	ry to a differ	ent reservoir51	Expires March 31, 1993 5. Lease Designation and Serial No. LC=029548-A 6. If Indian, Allottee or Tribe Name
	SUBMIT	IN TRIPLICATE		Ç 5.144	= N/A
1. Type of Well Solution Well Well Other Well Other Well Other					 7. If Unit or CA, Agreement Designation N/A
2. Name of Operator DEVON ENERGY OPERATING CORPORATION					8. Well Name and No.
3. Address and Telephone No 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405)552-4527					C. A. Russell #18 9. API Well No. 30-015-28794
 Location of Well (Footage. Sec., T., R., M., or Survey Description) 330' FNL & 1350' FEL, Sec. 18-17S-31E 					 10. Field and Pool, or Exploratory Area Grayburg Jackson 11. County or Parish, State Eddy County, NM
CHECK APP	ROPRIATE BOX(s	TO INDICATE NA	TURE OF	NOTICE, REPO	ORT, OR OTHER DATA
	TYPE OF SUBMISSION TYPE OF ACTION				
 Notice of Intent Subsequent Report 		Abandon Recomple	tion	ECEIVI	Change of Plans Change of Plans New Construction Fracturing
Final Abandonment Notic	e	Casing Ro			Conversion to Injection Dispose Water Note: Report results of multiple completion on Well
13. Describe Proposed or Complet locations and measured and	d Operations (Clearly state all per true vertical depths for all markers	inent details, and give pertinent c and zones pertinent to this work.	iates, including esti	L CON.	Completion or Recompletion Report and Log form.) posed work. If well is directionally drilled, give subsurfied
	2:30 p.m., 2/4/96. 13 3/8" surface csg @ 306'.		+ 1 piece, 1	DIST. 2	0, ST&C, 323.22'. Csg shoe
Cem	5#/sk Gil, (wt 12	.7 ppg, yield 1.86 d	cft/sk). Tai	led in w/275 sx (1/4 lb/sk celloseal + 2% CaCl + Class "C" + 2% CaCl, (wt 14.8 mt. Circ'd 12 sx to surface.
Ran	of 3800' on 2/10/9 5 1/2" prod csg as collar @ 3751'. ented csg as follows (wt 13 ppg, yield	6. follows: 87 jts 5 1/ Fop - 76 jts, 3394.(s: Lead w/1250 sx	/2", 15.50#)2', middle : PSL "C" + d in w/250	J-55, 8rd LT&C - 1 jt, 18.20', bc - 4% gel + 5% sa sx Class "H" + 1	 C. Float shoe @ 3799', float ottom - 9 jts, 401.83'. alt + 1/4 lb/sk celloflake, 0% Thizad + 1/4 lb/sk
14. Thereby certify that the for- Signed Karen	Byers		AREN BYERS NGINEERING T	ECHNICIAN	Date 2/13/96
(This space for Federal or State Approved by	omce use	Title			Date
Conditions of approval, if any:					

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to