Form 3160-5 (June 1990)

any matter within its jurisdiction.

UNITO STATES DEPARTMEN. OF THE INTERIOR BUREAU OF LAND MANAGEMENT



FORM APPROVED

Boltzhio		Budget Bureau No. 1004-0135 Expires March 31, 1993
SUNDRY NOTI	ICES AND REPORTS ON WELLS	5. Lease Designation and Serial No.
Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.		LC-029548-A
Use "APPLICATION	N FOR PERMIT—" for such proposals	6. If Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE		N/A
1. Type of Well		7. If Unit or CA, Agreement Designation
1. Type of Well Gas Well Other		N/A
2. Name of Operator DEVON ENERGY OPERATING CORPORATION		8. Well Name and No.
3. Address and Telephone No.	7	C. A. Russell # 12
20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405)552-4527		30-015-28809
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		10. Field and Pool, or Exploratory Area
330' FNL & 2050' FWL, Sec. 18-17S-31E		Grayburg Jackson Q, SR, GB, SA
		11. County or Parish, State
14 172 187 2 18 18 18 18 18 18 18 18 18 18 18 18 18		Eddy County, NM
CHECK APPROPRIATE BO	DX(s) TO INDICATE NATURE OF NOTICE, REF	PORT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent	Abandonment	Change of Plans
Notice of Intern	Recompletion	New Construction
Subsequent Report	Plugging Back	Non-Routine Fracturing
	Casing Repair	Water Shut-Off
Final Abandonment Notice	Altering Casing	Conversion to Injection
	Other Spud, TD'd & set csg	Dispose Water
		(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
13 Describe Proposed or Completed Operations (Clearly stat locations and measured and true vertical depths for all	te all pertinent details, and give pertinent dates, including estimated date of starting any markers and zones pertinent to this work.)*	proposed work. If well is directionally distled, give subsurface
·	•	TO BORNIES
Spud well @3:00 p.m., 2/12/96.		RECEIVED)
Ran 13 3/8" surface csg	as follows: 6 jts + 1 piece of 13 3/8", 48#, H-40, 8rd ST&C, 30	6.94'. Csg shoe @ 314'.
Cemented csg as follows	: Lead w/400 sx PSL "C" + 6% gel + 2% $CaCl_2$ + 1/4 lb/sk cell iled in w/275 sx Cl "C" + 2% $CaCl_2$, (wt 14.8 ppg, yield 1.34 cf	oflake + 54/9k gilsonite (yt 12.7 ppg, yield
1.86 cft/sk). Ta	iled in $w/275$ sx Cl "C" + 2% CaCl ₂ , (wt 14.8 ppg, yield 1.34 cf	Vsk). Top off chat w/11000 - 400 sx Class
"C". Circ'd 10 Squeezed 13 3/8" csg sho		011 0000 513
Ran 8 5/8" intermediate	De w/200 sx Class "C". csg as follows: 36 jts 8 5/8", 24#, J-55, 8rd ST&C, 1458.90'.	Cso show
Cemented csg as follows:	: Lead w/400 sx POZ "C" + 6% gel + 2% CaCl ₂ + 1/4 lb/sk cel	loseal. (wt 12.7 pog. vield 1.86 cft/sk)
Tailed in w/ 200	0 sx Class "C" + 2% CaCl ₂ , (wt 14.8 ppg, yield 1.34 cft/sk). To	p off cmt w/1" tbg - 200 sx Class "C" + 3%
CaCl ₂ . Circ'd 1	17 sx to pit.	
Reached TD of 3785' on 2/21/96.		
	ollows: 88 jts, 5 1/2", 15.50#, J-55, 8rd LT&C. Csg shoe @ 37	84', Float collar @ 3738'. Top - 78 its.
3364.26'; middl	le - 1 jt, 30.87'; bottom - 9 jts, 395.56'.	,
Cemented csg as follows:	: Lead w/400 sx POZ "C" + 4% gel + 5% salt + 1/4 lb/sk cellos	seal, (wt 13 ppg, yield 1.76 cft/sk). Tailed in
w/275 sx Class s	"H" + 10% Gypsum + 1/4 lb/sk celloseal, (wt 14.5 ppg, yield 1	52 cft/sk). Circ'd 61 sx to surface.
14. I hereby certify that the foregoing is true and corr		
Vaca. R	KAREN BYERS FNGINFERING TECHNICIAN	
Signed March Duch	Title ENGINEERING TECHNICIAN	Date 2/23/96
(This space for Federal or State office use)		
Approved by	Title	Date
Conditions of approval, if any:		

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to