Form 3160-5 (June 1990)		D STATES N. M. Oil Con OF THE INTERIOR 811 S. 1ST ST	Division
		ND MANAGEMENT ARTESIA, NM 88210	
	5. Lease Designation and Serial No.		
Do not use this fo	LC-031844		
	6. If Indian, Allottee or Tribe Name		
	SUBMIT IN	N TRIPLICATE	N/A
1. Type of Well	7. If Unit or CA, Agreement Designation		
N2Í0i ⊓	Gas Dother /		N/A
2. Name of Operator		rs EASE MARS	8. Well Name and No.
			Fren Oil Co. #23
3. Address and Telephon	9. API Well No.		
20 NORTH BROA	ADWAY, SUITE 1500, OKLAHOM	а сіту, окlahoma 73102 (405)552-4527 JUL 2 с 1995	30-015-28822
4. Location of Well (Fo	otage. Sec., T., R., M., or Survey Descr	10. Field and Pool, or Exploratory Area	
10' FSL & 1475' FEL, Sec. 19-17S-31E			Grayburg Jackson
		Oll cere. 20	U a 11. County or Parish, State
			Eddy County, NM
CHECK A	APPROPRIATE BOX(s)	TO INDICATE NATURE OF NOTICE, RE	PORT, OR OTHER DATA
	TYPE OF SUBMISSION TYPE OF ACTION		
Notice of Intent		Abandonment	Change of Plans
57		Recompletion	New Construction
Subsequent Report		Plugging Back	Non-Routine Fracturing
	Notice	Casing Repair	Water Shut-Off
Final Abandonment Notice		Altering Casing	Conversion to Injection
		Other Spud, TD'd & set csg	Dispose Water (Note: Report results of multiple completion on Well
<u></u>			Completion or Recompletion Report and Log form.)

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

## Spud well @ 7:30 p.m., 6/12/96.

Ran surface csg as follows: 9 jts, 8 5/8", 24#, J-55, ST&C, 381.14'. Csg shoe 396'. Cemented csg as follows: Lead - 150 sx 35/65 POZ "C" + 6% gel + 2% CaCl<sub>s</sub> + 1/4 lb/sk celloflake, (wt 12.7 ppg, yield 1.86 cft/sk). <u>Tail</u> - 200 sx Class "C" + 2% CaCl<sub>2</sub>, (wt 14.8 ppg, yield 1.32 cft/sk). Circ'd cmt to surface.

## Reached TD of 3735' on 6/19/96.

Ran production csg as follows: 88 jts, 5 1/2", 15.50#, J-55, LT&C, Float shoe @ 3734', float collar @ 3687' Top - 78 jts, 3319.61'; middle 1 jt, 39.20'; bottom 9 jts, 389.29'.

Cemented csg as follows: Lead - 1150 sx 35/65 POZ "C" + 4% gel + 5% salt + 1/4 lb/sk celloflake, (wt 13 ppg, yield 1.76 cft/sk). <u>Tail</u> - 325 sx Class "H" + 10% Thixad + 1/4 lb/sk celloflake, (wt 14.5 ppg, yield 1.52 cft/sk). **TOC** @ approx 150'.

14. I hereby certify that the foregoing is true and correct			
	KAREN BYERS tle <u>ENGINEERING TECHNICIAN</u> Date <u>07/12/96</u>		
(This space for Federal or State office use)	ACCEPTED FORRECORD		
Approved by Ti Conditions of approval, if any:	the Alffeld Bate Date		
	BLM		
Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to			