Form 3160-5 (June 1990)

UNI) STATES DEPARTMEN 1 OF THE INTERIOR BUREAU OF LAND MANAGEMENT



FORM APPROVED

Budget Bureau No. 1004-0135 Expires March 31, 1993 5. Lease Designation and Serial No. SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. LC-029548A Use "APPLICATION FOR PERMIT—" for such proposals 6. If Indian, Allottee or Tribe Name SUBMIT IN TRIPLICATE 7. If Unit or CA, Agreement Designation Type of Well ⊠ Oil Weil ☐ Gas Well Other 8. Well Name and No. 2. Name of Operator **DEVON ENERGY OPERATING CORPORATION** C. A. Russell #17 3. Address and Telephone No. 9. API Well No. 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405)552,452 30-015-28835 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 2332' FNL & 330' FWL, Sec. 18-17S-31E Grayburg Jackson 11. County or Parish, State Eddy County, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Plans Recompletion New Construction Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Final Abandonment Notice Altering Casing of the property of the property of Other Spud, TD'd & set csg 13 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed locations and measured and true vertical depths for all markers and zones pertinent to this work.)* OIL COM. DIV. Spud well @ 9:15 a.m., 3/31/96. Ran 8 5/8" csg as follows: 10 jts, 8 5/8", 24#, J-55, ST&C, 406.81'. Csg shop@s420'2 Cemented csg as follows: Lead - 150 sx 35/65 "C" + 6% gel + 2% CaCl₂, (wt 12.7 ppg, yield 1.86 cft/sk). Tail - 200 sx Class "C" + 2% CaCl₂, (wt 14.8 ppg, yield 1.32 cft/sk). Circ'd cmt to surface. Reached TD of 3820' on 4/5/96. Ran 5 1/2" csg as follows: 89 jts, 5 1/2", 15.50#, J-55, LT&C. Csg shoe @ 3819', float collar @ 3775'. Top - 79 jts, 3403.89', middle - 1 jt, 37.05'; & bottom - 9 jts, 380.54'. Cemented csg as follows: Lead - 800 sx 35/65 POZ "C" + 4% gel + 5% salt + 1/4 lb/sk celloseal, (wt 13 ppg, yield 1.76 cft/sk). Tail - 300 sx Class "H" + 10% Gypsum + 1/4 lb/sk celloseal. (wt 14.5 ppg, yield 1.52 cft/sk). Circ'd cmt to surface. 14. I hereby certify that the foregoing is true and correct KAREN BYERS ENGINEERING TECHNICIAN Approved by Conditions of approval, if any: