orm 3160-5 June 1990)

UNIT" STATES DEPARTMENT OF THE INTERIOR

OIL C SERVATION DIV 811 S. 1st ST.

CIST

ARTESIA, NM 882102034PROVED **BUREAU OF LAND MANAGEMENT** Budget Bureau No. 1004-0135 Expires March 31, 1993 5. Lease Designation and Serial No. SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. LC-054908 Use "APPLICATION FOR PERMIT—" for such proposals 6. If Indian, Allottee or Tribe Name SUBMIT IN TRIPLICATE 7. If Unit or CA, Agreement Designation 1. Type of Well ☐ Gas Well ⊠ Oil Well Other 8. Well Name and No. 2. Name of Operator **DEVON ENERGY OPERATING CORPORATION** Hudson Federal #8 3. Address and Telephone No. 9. API Well No. 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405)552-4527 30-015-28888 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage. Sec., T., R., M., or Survey Description) Grayburg Jackson 1475' FNL & 990' FWL, Sec. 17-17S-31E 11. County or Parish, State Eddy County, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION TYPE OF SUBMISSION Notice of Intent Abandonment Change of Plans Recompletion **New Construction** Plugging Back Non-Routine Fracturing Subsequent Report Casing Repair Water Shut-Off Altering Casing Conversion to Injection Final Abandonment Notice Other Spud, TD'd & set csg Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Spud well @ 7:30 p.m., 5/10/96. Ran surface csg as follows: 10 jts 8 5/8", 24#, J-55 ST&C, 405'. Csg shoe @ 420'. Cmt'd csg as follows: Lead - 175 sx PSL "C" + 4% gel + 2% $CaCl_2 + 1/4$ #/sk celloseal, (wt 12.7 ppg, yield 1.86 cft/sk). Tail - 200 sx Class "C" + 2% CaCl₂, (wt 14.8 ppg, yield 1.32 cft/sk). Circ'd cmt to surface. Reached TD of 3870' @ 6:30 a.m., 5/17/96. Ran prod csg as follows: 91 its 5 1/2", 15.5#, J-55 LT&C. Csg shoe @ 3869', float collar @ 3822'. Top - 81 jts, 3463.66'; middle - 1 jt, 14.34'; bottom - 9 jts, 390.82'. Cmt'd csg as follows: Lead - 1100 sx PSL "C" + 4% gel + 5% salt + 1/4 #/sk celloseal, (wt 13 ppg. yield 1.76 cft/sk). Tail - 350 sx Class "H" + 10% Gypsum + 1/4 #/sk celloseal, (wt 14.5 ppg, yield 1.52 cft/sk). **TOC** @ +/- 130'.

14. I hereby certify that the foregoing is true and correct Signed Hom Bull	KAREN BYERS Title ENGINEERING TECHNICIAN	Date <u>06/06/96</u>
(This space for Federal or State office use)		
Approved byConditions of approval, if any:	Title	Date

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or faudulent statements or representations as to any matter within its jurisdiction