Form 3160-5 (June 1990)

UNIT STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

OIL CONS YATION DIV

811 S. 1st S .. ARTESIA, NM 88210-2834
Budget Bureau No. 1004-0135
Expires March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals SUBMIT IN TRIPLICATE 1. Type of Well Soil		5. Lease Designation and Serial No.
		LC-029395-A
		6. If Indian, Allottee or Tribe Name
		N/A
		7. If Unit or CA, Agreement Designation
		N/A
		8. Well Name and No.
		Turner A #45
		9. API Well No.
		30-015-28890
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		10. Field and Pool, or Exploratory Area
975' FNL & 1450' FWL, Sec. 19-17S-31E		
		Grayburg Jackson 11. County or Parish, State
	<u> </u>	
		Eddy County, NM
CHECK ADDDODDIATE BOY'S	TO INDICATE MATINE OF MOTION AND	OORT OR OTHER DATA
TYPE OF SUBMISSION) TO INDICATE NATURE OF NOTICE, REF	
TIPE OF SUBMISSION	TYPE OF ACTION	· · · · · · · · · · · · · · · · · · ·
Notice of Intent	Abandonment	Change of Plans
	Recompletion	New Construction
Subsequent Report	Plugging Back	Non-Routine Fracturing
_	Casing Repair	Water Shut-Off
Final Abandonment Notice	Altering Casing	Conversion to Injection
	Other Spud, TD'd & set csg	Dispose Water
		(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
3 Describe Proposed or Completed Operations (Clearly state all per	rtinent details, and give pertinent dates, including estimated date of starting any	proposed work. If well is directionally drilled, give subsurface
locations and measured and true vertical depths for all marker	s and zones pertinent to this work.)*	
Spud well @ 4:00 p.m., 5/14/9	6.	
Ran surf csg as follows	: 8 jts 8 5/8", 24#, J-55 ST&C, 338.29'. Csj	g shoe @ 352'.
	s: <u>Lead</u> - 150 sx POZ "C" + 6% gel + 2% C	
nng vield 1.87 c	ft/sk). <u>Tail</u> - 200 sx Class "C" + 2% CaCl ₂ , (14.0 mg spield 1.22 a\(\text{C}_1\)
Circ'd cmt to su		14.8 ppg, yield 1.32 cli/sk).
Circ d cint to su	iriace.	
December TD -62(04) @ 1.00		
Reached TD of 3684' @ 1:00]	•	
Ran prod csg as follows	s: 87 jts 5 1/2", 15.5#, J-55 LT&C. Csg sho	e @ 3683', float collar @ 3638'.
Top - 77 jts, 329	5.46'; middle - 1 jt, 14.25'; bottom - 9 jts, 37	4.87'.
	s: <u>Lead</u> - 1600 sx PSL "C" + 4% gel + 5% s	
ppg. vield 1.76 c	ft/sk). <u>Tail</u> - 400 sx Class "H" + 10% Gypsu	m + 1/4 #/sk celloseal (vat 14 5
	ft/sk). Circ'd cmt to surface.	It in the concean, (with 14.3
ppg, yield 1.32 cl	disk). Circ d cirit to surface.	
4. I hereby certify that the foregoing is true and correct		
Nonna Russa	KAREN BYERS	
Signed Paris Dude	Title ENGINEERING TECHNICIAN	Date <u>06/07/96</u>
This space for Federal or State office use)		
Approved by	Title	De la la companya de la companya della companya della companya de la companya della companya del
Conditions of approval, if any:	Title	Date