

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

OIL CONSERVATION DIV
811 S. 1st ST.
ARTESIA, NM 88210-2899

FORM APPROVED
Bureau No. 1004-0135
Expires March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator
DEVON ENERGY OPERATING CORPORATION

3. Address and Telephone No.
20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405)552-4527

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
925' FNL & 2600' FWL, Sec. 19-17S-31E

5. Lease Designation and Serial No. LC-029395-A
6. If Indian, Allottee or Tribe Name N/A
7. If Unit or CA, Agreement Designation N/A
8. Well Name and No. Turner A #46
9. API Well No. 30-015-28891
10. Field and Pool, or Exploratory Area Grayburg Jackson
11. County or Parish, State Eddy County, NM

RECEIVED

JUN 11 1996

CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Plugging Back
	<input type="checkbox"/> Casing Repair
	<input type="checkbox"/> Altering Casing
	<input checked="" type="checkbox"/> Other Spud, TD'd & set csg
	<input type="checkbox"/> Change of Plans
	<input type="checkbox"/> New Construction
	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Water Shut-Off
	<input type="checkbox"/> Conversion to Injection
	<input type="checkbox"/> Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud well @ 1:00 p.m., 4/30/96.

Ran surface csg as follows: 9 jts, 8 5/8", 24#, J-55, ST&C, 370.81'. Guide shoe @ 388'.

Cemented csg as follows: Lead - 300 sx 35/65 POZ "C" + 6% gel + 2% CaCl₂ + 1/4 lb/sk celloseal, (wt 12.7 ppg, yield 1.93 cft/sk). Tail - 200 sx Class "C" + 2% CaCl₂, (wt 14.8 ppg, yield 1.32 cft/sk). Cmt'd via 1" pipe w/275 sx Class "C". Circ'd cmt to surface.

Reached TD of 3670' @ 8:30 a.m., 5/6/96.

Ran production csg as follows: 86 jts, 5 1/2", 15.50#, J-55, LT&C. Float shoe @ 3669', float collar 3624'. Top - 76 jts, 3245.61'; middle - 1 jt, 38.02'; bottom - 9 jts, 387.39'.

Cemented csg as follows: Lead - 1800 sx PSL "C" + 4% gel + 5% salt + 1/4 lb/sk celloseal, (wt 13 ppg, yield 1.76 cft/sk). Tail - 325 sx Class "H" + 10% Gypsum + 1/4 lb/sk celloseal, (wt 14.5 ppg, yield 1.52 cft/sk). PBTD @ 3397', 227' cmt in csg. Circ'd cmt to surface.

14. I hereby certify that the foregoing is true and correct

Signed Karen Byers
(This space for Federal or State office use)

KAREN BYERS
Title ENGINEERING TECHNICIAN

Date 05/17/96

Approved by _____
Conditions of approval, if any:

Title _____

FILED FOR RECORD
JUN - 7 1996
CARLSBAD, NEW MEXICO

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side