Form 3160-5 (June 1990)

## UNIT STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

OIL CONSERVATION DIV 811 S. 1st ST.

0197

ARTESIA, NM 88210-2834
FORM APPROVED
Budget Bureau No 1004-0135
Expires March 31 1993

SUNDRY NOTICES	S AND REPORTS ON WELLS	5. Lease Designation and Serial No.
	or to deepen or reentry to a different reservoir.	LC-029395-A
Use "APPLICATION FOR PERMIT—" for such proposals  SUBMIT IN TRIPLICATE		6. If Indian, Allottee or Tribe Name     N/A     7. If Unit or CA, Agreement Designation
Name of Operator DEVON ENERGY OPERATING CORPORA	MAY 2-9-1255	8. Well Name and No.  Turner A #42
Address and Telephone No.  20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405)552-4527  Location of Well (Footage, Sec., T., R., M., or Survey Description)  300' FSL & 2650' FWL, Unit O, Sec. 18-17S-31E		9. API Well No.
		30.015.38016
		30-015-28916  10. Field and Pool, or Exploratory Area
		Grayburg Jackson (Q-SR-GB-SA)  11. County or Parish, State
		Eddy County, NM
CHECK APPROPRIATE BOX(s	) TO INDICATE NATURE OF NOTICE, REP	ORT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	1
Notice of Intent	Abandonment	Change of Plans
_	Recompletion	New Construction
Subsequent Report	Plugging Back	Non-Routine Fracturing
<b>7</b>	Casing Repair	Water Shut-Off
Final Abandonment Notice	Altering Casing	Conversion to Injection
	Other Spud, TD'd & set csg	Dispose Water
		(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
3 Describe Proposed or Completed Operations (Clearly state all pelocations and measured and true vertical depths for all marker	rtinent details, and give pertinent dates, including estimated date of starting any p is and zones pertinent to this work.)*	roposed work. If well is directionally drilled, give subsurface
Spud well @ 3:30 p.m., 4/22/9	6.	
Ran surface csg as follo	ows: 10 jts, 8 5/8", 24#, J-55, ST&C, 406.53	Guide shoe @ 422'
Cemented csg as follow	vs: Lead 1 - 150 sx 35/65 "C" + 6% gel + 2%	$C_3C_1 + 1/4$ lb/sk callocal + 5
lh/sk Gilsonite (s	wt 12.7 ppg, yield 1.93 cft/sk). Lead 2 - 150	- CaC <sub>12</sub> + 1/4 10/5k Celloseal + 3
+ 1/4 lb/sk collect	wit 12.7 ppg, yield 1.95 cli/sk). Lead 2 - 150;	$3x 33/03 + 6\% \text{ gel} + 2\% \text{ CaCl}_2$
1/4 10/5K CEROS	seal, (wt 12.7 ppg, yield 1.93 cft/sk). Tail - 20	$0 \text{ sx Cl } \text{"C"} + 2\% \text{ CaCl}_2$ , (wt 14.8)
ppg, yieid 1.32 c	ft/sk). Topped off via 1" w/250 sx Cl "C" + 4	% CaCl <sub>2</sub> . Circ'd cmt to surface.
Reached TD of 3760' @ 1:30 a	a.m., 4/29/96.	
	follows: 88 jts, 5 1/2", 15.50#, J-55, LT&C.	Float shoe @ 3750' float collar
3720' Ton - 78	jts, 3369.13'; middle - 1 jt, 21.97'; bottom - 9	) ita 260 47'
Camented esq as follow	7025 av 25/65 DOZ "C" + 40/ - 1	, Jts, 309.47
12 nng wield 1.7	vs: Lead - 2025 sx 35/65 POZ "C" + 4% gel -	7 3% sait + 1/4 lb/sk celloseal, (wt
15 ppg, yield 1.7	6 cft/sk). Tail - 300 sx "H" + 10% Gypsum +	1/4 lb/sk celloseal, (wt 14.5 ppg,
yield 1.52 cft/sk)	Circ'd cmt to surface.	
4. I hereby certify that the foregoing is true and correct	VADENI DVEDG	
igned Kanon Bueno	KAREN BYERS  Title ENGINEERING TECHNICIAN	Data05/02/07
This space for Federal or State office use)	ARIO	Date <u>05/02/96</u>
pproved by	Title	Date
onditions of approval, if any:		24

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to