Form 3160-5 (June 1990)

Approved by

Conditions of approval, if any:

UNIT STATES DEPARTMEN'I OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

OIL COT RVATION DIV 811 S. 1st ST.

ARTESIA, NM 88210-2507M APPROVED

Expires March 31 1993 5. Lease Designation and Serial No. SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. LC-029548-A Use "APPLICATION FOR PERMIT—" for such proposals 6. If Indian, Allottee or Tribe Name SUBMIT IN TRIPLICATE 7. If Unit or CA, Agreement Designation 1. Type of Well ☐ Gas - Other 8. Well Name and No. 2. Name of Operator **DEVON ENERGY OPERATING CORPORATION** C. A. Russell #19 API Well No. 3. Address and Telephone No. 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405) \$2 015-28924 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage. Sec., T., R., M., or Survey Description) JUN 111**199**6 1310' FNL & 2150' FEL, Sec. 18-17S-31E Grayburg-Jackson 11. County or Parish, State D Hady County, NM $(C(0)N)_{a}$ CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE RÉPORT. OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Plans Recompletion New Construction Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Final Abandonment Notice Altering Casing Conversion to Injection Other Spud, TD'd & set csg Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Spud well @ 3:30 p.m., 5/2/96. Ran surface csg as follows: 9 jts, 8 5/8", 24#, J-55, ST&C, 370.31'. Guide shoe @ 386' Cemented csg as follows: Lead - 300 sx 65/35 POZ "C" + 6% gel + 2% CaCl₂ + 1/4 lb/sk celloseal. (wt 12.7 ppg, yield 1.86 cft/sk). Tail - 200 sx Class "C" + 2% CaCl₂, (wt 14.8 ppg, yield 1.32 cft/sk). Circ'd cmt to surface. Reached TD of 3820' @ 2:00 a.m., 5/9/96. Ran production csg as follows: 89 jts, 5 1/2", 15.50#, J-55, LT&C. Float shoe @ 3819', float collar 3778'. Top - 79 jts, 3417.67; middle - 1 jt, 39.01', bottom - 9 jts, 380.32' Cemented csg as follows: Lead - 625 sx PSL "C" + 4% gel + 5% salt + 1/4 lb/sk celloseal, (wt 13 ppg. yield 1.76 cft/sk). Tail - 350 sx "H" + 10% Gypsum + 1/4 lb/sk celloseal, (wt 14.5 ppg. yield 1.52 cft/sk). Circ'd cmt to surface. 14. I hereby certify that the foregoing is true and correct KAREN BYERS Title ENGINEERING TECHNICIAN

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious of fraudulent statements or representations as to any matter within its jurisdiction