

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):				38. GEOLOGIC MARKERS		
FORMATION	IOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	MEAS. DEPTH	TRUE VERT. DEPTH
Rustler	312	460	ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.. (continued from the front)			
Salado	460	1288				
Tansill	1288	1446				
Yates	1446	1753				
Seven Rivers	1753	2362				
Queen (Artesia)	2362	2738				
Grayburg	2738	3063				
San Andres	3063	3800 (TD)				
		DEPTH				
		2700'	22,000 gals Spectra Frac + 63,000# 20/40 Brady sand + 20,000# 16/30 resin coated sand.			
		2700'	Acidized w/150 gals 15% HCl acid.			
		2799'-2956'	Squeezed perms w/125 sx Class "C" cement.			
		2799'-2956'	Acidized w/1500 gals 15% HCl acid.			
		2799'-2956'	Frac'd w/15,500 gals Spectra Frac + 33,000# 16/30 Brady sand + 12,000# 16/30 resin coated sand.			