

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE \*  
(Other Instructions on  
reverse side)

Budget Bureau No. 1004-0135  
Expires August 31, 1985

C/SF

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT - " for such proposals.)

N.M. Oil Cons. Division

811 S. 1st Street

Artesia, NM 88210-2804

5. LEASE DESIGNATION AND SERIAL NO.  
LC-029420-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Grayburg Jackson 7-Rivers

8. API WELL NO.

30-015-28972

9. WELL NO.

199

10. FIELD AND POOL, OR WILDCAT  
Grayburg Jackson 7-Rivers

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 15-T17S-R31E

14. PERMIT NO

15. ELEVATIONS (Show whether DF, RT, GR, etc.)  
3862'

12. COUNTY OR PARISH  
Eddy

13. STATE  
NM

16. Check Appropriate Box to indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT OFF

☐

PULL OR ALTER CASING

☐

FRACTURE TREAT

☐

MULTIPLE COMPLETE

☐

SHOOT OR ACIDIZE

☐

ABANDON\*

☐

REPAIR WELL

☐

CHANGE PLANS

☐

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐

REPAIRING WELL

☐

FRACTURE TREATMENT

☐

ALTERING CASING

☐

SHOOTING OR ACIDIZING

☐

ABANDONMENT \*

☐

(Other) Perforate & Acidize

☐

(Note: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS: (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

08/07/96 NU tbg. head & BOP. PU 4-3/4" crossover bit & 4 3-1/2" DC's. Drilled plug & 40' of cmt. to 160'.

08/08/96 Broke circulation. Changed bit to 4-3/4". Drilled to 788'.

08/09/96 Drilled cmt. f/788'-1653'. Circ clean.

08/12/96 Drilled cmt. f/1653'-2790'. Displaced hole w/FW.

08/13/96 Drilled cmt. f/2790'-3341'

08/14/96 Drilled f/3341'-3955'. Tagged float collar @ 3955'. TOH w/tbg. LD tbg. & drill collars. RDMO.

09/20/96 Halliburton perforated San Andres Three Fingers Upper Massive f/3725', 26', 27', 28', 29', 30', 42', 43', 44', 45', 59', 60', 61', 62' & 63' w/1.58" (15 holes).

09/23/96 Halliburton acidized San Andres Three Fingers f/3725'-3763' w/2300 gals 15% NE-FE acid & 30 ball sealers. Formation broke @ 5137#. Balled out w/45 bbls. acid in formation. MTP 5137# @ 4.3 bpm. ATP 2870# @ 3.6 bpm. ISIP 2196#. 5 min. 2093#. 10 min. 2044#. 15 min. 2000#.

18. I hereby certify that the foregoing is true and correct.

SIGNED Mary Jo Turner TITLE Completion Department DATE December 10, 1996

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

\*See Instruction On Reverse Side



