	•			-
(Formerly 9-331)	JNITED STATES MENT OF THE INTERIOR	N.M. Oil Cons 8975 ST STISTISTICS (Other Instructions on Artesisychemide 821)		clsf
BUREAL	J OF LAND MANAGEMENT		5. LEASE DESIGNATION AND SERIAL LC-029418-B	NO.
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.			6. IF INDIAN, ALLOTTEE OR TRIBE NA	AME
Use "APPLie	CATION FOR PERMIT - " for such proposa			
OIL GAS WELL U	OTHER	RECEIVE	Skelly Unit	
2. NAME OF OPERATOR The Wiser Oil Company		OCT - 3 1996	8. API WELL NO. 30-015-28974	<u></u>
3. ADDRESS OF OPERATOR	** ************************************		R. WELL NO.	
P. O. Box 2568 Hobbs, New Mexico 88241 OIL CON.			21 1256	
 LOCATION OF WELL (Report location clearly and in accordance with any State requirements. DIST. 2 			10. FIELD AND POOL, OR WILDCAT	
At surface 1403' FS	SL & 1387' FEL		Grayburg Jackson 7-Rivers 11. SEC., T., R., M., OR BLK. AND	
Sec. 23-7 Unit J	F17S-R31E		SURVEY OR AREA	
			Sec. 23-T17S-R31E	
14. PERMIT NO	15. ELEVATIONS (Show whether DF, R	T, GR, etc.)	12. COUNTY OR PARISH 13.	STATE
	3864' GR			NM
16. Check Appropriate Box to indicate Nature of Notice, Report, or Other Data				
NOTICE OF INTENTION TO: SUI			BSEQUENT REPORT OF:	
TEST WATER SHUT OFF	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL	
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CASING	
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	ABANDONMENT *	
REPAIR WELL	CHANGE PLANS	(Other) Spudding, Ceme	nting Surface & Production Casing	
(Note: Report results of			f multiple completion on Well	
17. DESCRIBE PROPOSED OR COMPLET proposed work. If well is directionally	ED OPERATIONS: (Clearly state all pertine drilled, give subsurface locations and measure	ent details, and give pertinent dates, ed and true vertical depths for all n	, including estimated date of starting any narkers and zones pertinent to this work.)	
10 jts. 8-5/8", 23#, K-55, LTa Flocele + 2% CaCl. Plug dov	& C csg. Set at 442'. Halliburt vn @ 4:15 a.m., 09/07/96. Circ	on cemented with 325 sx culated 76 sx. cmt. BLM	6/96. Drilled hole to 442'. Ran Class "C" containing 1/4#/sk. I was notified, no representative rs. Hit a water flow @ 1706' and	l
LT&C csg. Set at 4050'. Ha + 1/4# Flocele/sk. followed by bbl. FW + 12 bbls. MSA + 80 into water flow. Circ. 83 sx. 6 n m_09/11/96_ Released rig a	Illiburton cemented w/1000 gals. 250 sx. Premium Plus + 3#KC bbls. FW w/Lo Surf 300. Closent. Pressure tested casing to 1: t 12:45 a m .09/12/96. BLM w	Superflush 102 + 1000 L/sk. + .5% Halad 344 + sed valves on csg. w/4 bb 500# for 30 minutes, no	pressure loss. Plug down at 10:4.	5
18 I hereby certify that the foregoing is true ar	nd correct.			
signed Many Go Turry	TTTLE Drilling De	epartment	DATE September 17, 19	96
(This space for Federal or State office use)				
APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	TITLE		DATE	<u>.</u>
			CEPTED FOR RECORD	
*See Instruction On Reverse Side			GOT CANADA GLASS	
Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of statements or representations as to any matter within its jurisdiction.			CCT C 1. 1986 f the United States any false, fightious or frauda	ulent