

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Division
811 S. 1st Street
Artesia, NM 88210-2834

FORM APPROVED
Budget Bureau No. 1004-0135
Expires March 31, 1993
Designation and Serial No.

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

SUBMIT IN TRIPLICATE

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other
2. Name of Operator
DEVON ENERGY OPERATING CORPORATION

3. Address and Telephone No.
20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405)552-4527

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
560' FSL & 1880' FEL, Sec. 18-17S-31E

LC-029395-A
6. If Indian, Allottee or Tribe Name
N/A
7. If Unit or CA, Agreement Designation
N/A
8. Well Name and No.
Turner "A" #58
9. API Well No.
30-015-29001
10. Field and Pool, or Exploratory Area
Grayburg Jackson
11. County or Parish, State
Eddy County, NM

CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Plugging Back
	<input type="checkbox"/> Casing Repair
	<input type="checkbox"/> Altering Casing
	<input checked="" type="checkbox"/> Other Spud, TD'd & set csg
	<input type="checkbox"/> Change of Plans
	<input type="checkbox"/> New Construction
	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Water Shut-Off
	<input type="checkbox"/> Conversion to Injection
	<input type="checkbox"/> Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud well @ 7:00 p.m., 6/20/96.

Ran surface csg as follows: 9 jts, 8 5/8", 24#, J-55, ST&C, 379.87'. Guide shoe @ 396'.

Cemented csg as follows: Lead - 300 sx 35/65 POZ "C" + 6% gel + 2% CaCl₂ + 1/4 lb/sk celloflake, (wt 12.7 ppg, yield 1.86 cft/sk). Tail - 200 sx Class "C" + 2% CaCl₂, (wt 14.8 ppg, yield 1.32 cft/sk). Circ'd cmt to surface.

Reached TD of 3785' on 6/27/96.

Ran production csg as follows: 90 jts, 5 1/2", 15.50, J-55, LT&C. Float shoe @ 3784', float collar @ 3738'. Top - 80 jts, 3393.50'; middle - 1 jt, 14.30'; & bottom - 9 jts, 375.72'.

Cemented csg as follows: Lead - 1450 sx 35/65 POZ "C" + 4% gel + 5% salt + 1/4 lb/sk celloflake, (wt 13 ppg, yield 1.76 cft/sk). Tail - 300 sx Class "H" + 10% Thixad + 1/4 lb/sk celloflake, (wt. 14.5 ppg, yield 1.52 cft/sk). TOC @ 48'.

14. I hereby certify that the foregoing is true and correct

Signed Karen Byers
(This space for Federal or State office use)

KAREN BYERS
Title ENGINEERING TECHNICIAN

Date 07/25/96

Approved by
Conditions of approval, if any:

Title

Date