Form 3160-5
(November 1983)
(Formerly 9-331)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE \*
(Other Instructions on reverse side )

Budget Bureau No. 1004-0135 Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

35 65	P

			LC-029420-A		
SUNDRY NOT	ICES AND REPORTS O	WELLS Division	6. IF INDIAN, ALLOTTEE OR TR	IBE NAME	
(Do not use this form for pro	posals to drill or to deepen or plug back to CATION FOR PERMIT - " for such propositions."	different reservoir 13. UIVIS	Pit		
1.	LP LP	TO SEED OF EACH	7. UNIT AGREEMENT NAME	····	
OIL GAS WELL	OTHER \$\frac{1}{\psi}\$	Mosia, NM 88210-2 <b>83</b>	Skelly Unit		
2. NAME OF OPERATOR		MAR U 1 1997	8. API WELL NO.		
The Wiser Oil Company		THE CONTRACTOR OF THE CONTRACTOR	30-015-29092		
3. ADDRESS OF OPERATOR	(()	il Con. Div	9. WELL NO.		
P.O. Box 2568 Hobbs, N		raquirament	† 211 10. FIELD AND POOL, OR WILDO	NAT.	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  See also space 17 below.)  At surface  259' FSL & 1181' FWL  Sec. 15-T178-R31E			Grayburg Jackson 7-Rivers		
			11. SEC., T., R., M., OR BLK. AND		
			SURVEY OR AREA		
Unit M			0 15 71 70 70 10		
14. PERMIT NO	15. ELEVATIONS (Show whether DF, 1	RT. GR. etc.)	Sec. 15-T17S-R31E 12. COUNTY OR PARISH	13. STATE	
	3852' GR	,,	Eddy	NM	
6. Check A	Appropriate Box to indicate Natur	e of Notice, Report, or Other	· · · · · · · · · · · · · · · · · · ·	14141	
		1			
NOTICE OF INT	ENTION TO:	SU:	BSEQUENT REPORT OF:		
TEST WATER SHUT OFF	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL		
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CASING	;	
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	G ABANDONMENT *		
REPAIR WELL	CHANGE PLANS	(Other) Perforate & A			
(Other)		-	of multiple completion on Well sletion Report and Log form.)		
7. DESCRIBE PROPOSED OR COMPLET		nent details, and give pertinent dates	s, including estimated date of starting an		
11/27/96 Halliburton spotted 6 bbls. 15 15% NE-FE acid. Formation	drilled, give subsurface locations and measurements of NE-FE acid & perforated San Andres Up broke @ 3380#. Perfd. remaining Vacuum	pper Vacuum f/3451', 55' & 56' w. n & Grayburg f/3385'-88', 3410'-1	/1 SPF (3 holes). Broke perfs. & pumpe 12', 19'-23', 31', 33'-37', 40', 43', 44',	d 3 bbls. & 47' w/1	
	n Andres Upper Vacuum & Lower Graybur P 2650# @ 5.1 bpm. ISIP 1910#. 5 min.			n formation.	
12/07/96 Ran 2-7/8" tbg. to 3841'. SN	I @ 3805'. TAC @ 3415'. Ran 2-1/2" x I	-1/2" x 20' RHBC pump,			
		Walteren tos seausi			
	ga	In more and			
		The state of the s	34 <b>4.35</b>		
8. I hereby certify that the foregoing is true ar	nd correct.	Andrew St. 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			
SIGNED Many Go Tunger	TITLE Completion	n Department	DATEDecember 7, 199	<u>6</u>	
(This space for Federal or State office use)	VI. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1.				
ADDROVED DV	тіті е		DATE		
APPROVED BY	TITLE		DATE	<del></del>	
,					