

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE \*  
(Other Instructions on  
reverse side)

Budget Bureau No. 1004-0135  
Expires August 31, 1985

CLSP

SUNDRY NOTICES AND REPORTS ON WELL

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.)

Use "APPLICATION FOR PERMIT - " for such operations.

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. W-029420-A	
2. NAME OF OPERATOR The Wiser Oil Company		6. IF INDIAN, ALLOTTEE OR TRIBE NAME 32 AM '96	
3. ADDRESS OF OPERATOR P. O. Box 2568 Hobbs, New Mexico 88241		7. UNIT AGREEMENT NAME Skelly Unit	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1401' FNL & 1338' FWL Sec. 15-T17S-R31E Unit F		8. API WELL NO. 30-015-29203	
		9. WELL NO. 180	
		10. FIELD AND POOL, OR WILDCAT Grayburg Jackson 7-Rivers	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 15-T17S-R31E	
14. PERMIT NO	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3878'	12. COUNTY OR PARISH Eddy	13. STATE NM

16. Check Appropriate Box to indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT OFF <input type="checkbox"/>	PULL OR ALTER CASING <input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	MULTIPLE COMPLETE <input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	ABANDON* <input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF <input type="checkbox"/>	REPAIRING WELL <input type="checkbox"/>
FRACTURE TREATMENT <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
SHOOTING OR ACIDIZING <input type="checkbox"/>	ABANDONMENT * <input type="checkbox"/>

(Other) Spudding, Cementing Surface & Production Casing

(Note: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS: (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

MIRU Norton Drilling Co., Rig #5. Spudded 12-1/4" surface hole @ 10:45 a.m., 12/06/96. Drilled hole to 450'. Ran 10 jts. 8-5/8", 20#, ISW-42 ST&C csg. Set at 448'. Halliburton cemented with 325 sx. Class "C" containing 1/4#/sk. Flocele + 2% CaCl. Plug down @ 6:15 p.m., 12/06/96. Circulated 57 sx. cmt. BLM was notified, no representative present. NU BOP & tested csg. to 1000# for 30 minutes, no pressure loss. WOC 12 hrs.

Drilled 7-7/8" production hole to a depth of 3950'. Ran casing as follows: Ran 94 jts. 5-1/2" 17#, J-55, LT&C csg. Set at 3950'. Halliburton cemented w/1000 gals. Superflush 102 + 750 sx. Halliburton Lite + 8# salt/sk. + 1/4# Flocele/sk. followed by 250 sx. Premium Plus w/3#KCL/sk. + .5% Halad 344 + 1/4# Flocele/sk. Displaced w/1 bbl. FW + 12 bbls. MSA + 78 bbls. FW w/Lo-Surf 300. Plug down at 8:45 a.m. 12/11/96. Circ. 130 sx. cmt. Pressure tested casing to 1500# for 30 minutes, no pressure loss. Released rig at 10:45 a.m. 12/11/96. BLM was notified, no representative present.

18. I hereby certify that the foregoing is true and correct.

SIGNED Mary Jo Turner TITLE Drilling Department DATE December 12, 1996

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD  
DATE

DEC 13 1996

\*See Instruction On Reverse Side

