Form 3160-5 (November 1983) (Formerly 9-331)

N.M. Oil Cons. Dirition

UNITED STATES 811 S. (College Management of The INTERIOR Artesia, NYMero 822-10-2834 Budget Bureau No. 1004-0135 Expires August 31, 1985

RIDEALLOF LAND MANAGEMENT			5. LEASE DESIGNATION AND SERIAL NO.		
			LC-029418-A		
SUNDRY NOTICES AND REPORTS ON WELLS			6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir			, =====================================	ADD WAVE	
Use "APPLI	CATION FOR PERMIT - " for such propos	613 0 35 TM '95			
OIL GAS OTHER WELL			7. UNIT AGREEMENT NAME Skelly Unit		
					2. NAME OF OPERATOR
The Wiser Oil Company			30-015-29223		
3. ADDRESS OF OPERATOR			9. WELL NO.		
P. O. Box 2568 Hobbs, New Mexico 88241			216		
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1300' FSL & 2539' FWL Sec. 14-T17S-R31E Unit N			10. FIELD AND POOL, OR WILDCAT		
			Grayburg Jackson 7-Rivers		
			14. SEC., T., R., M., OR BLK. AND		
			SURVEY OR AREA		
			Sec. 14-T17S-R31E		
14. PERMIT NO	15. ELEVATIONS (Show whether DF, F	RT. GR. etc.)	12. COUNTY OR PARISH	13. STATE	
·	3883'	,,	Eddy	NM	
16. Check A	Appropriate Box to indicate Natur	e of Notice, Report, or Othe	r Data	IVIVI	
Nomen of a series					
NOTICE OF INTENTION TO:			BSEQUENT REPORT OF:		
TEST WATER SHUT OFF	PULL OR ALTER CASING	WATER OUT OF			
	├ ─-	WATER SHUT-OFF	REPAIRING WELL	· 📙	
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CASIN	G	
SHOOT OR ACIDIZE	ABANDON*	CHOOTING OF ACTIVITIES			
[-]	A EXAMPLE A	SHOOTING OR ACIDIZING	ABANDONMENT	•	
REPAIR WELL CHANGE PLANS (Other) Spudding, Cem		(Other) Spudding, Ceme	nenting Surface & Production Casing		
(Note: Report results o			of multiple completion on Well		
17. DESCRIBE PROPOSED OR COMPLET	ED OPERATIONS: (Clearly state all parti-	Completion or Recomp	oletion Report and Log form.)	·····	
proposed work. If well is directionally	drilled, give subsurface locations and measur	red and true vertical depths for all m	including estimated date of starting at narkers and zones pertinent to this world	iy.	
				·	
MIRU Norton Drilling Co., R	tig #7. Spudded 12-1/4" surface	e hole @ 6:15 p.m., 12/0	6/96. Drilled hole to 444'	Ran	
10 Jts. 8-3/8", 20#, ISW-42 S	T& C csg. Set at 440'. Hallib	urton cemented with 325 s	sx Class "C" containing 1.	/A#/eV	
Flocele + 2% CaCl. Plug dov	wn @ 3:30 a.m, 12/07/96. Cir	culated 103 sx. cmt. BL	M was notified no represen	ntativa	
present. NU BOP & tested cs	sg. to 1000# for 30 minutes, no	pressure loss. WOC 12 h	ers	nauvc	
		F			
Drilled 7-7/8" production hole	to a depth of 4100'. Ran casin	no as follows: Ran 07 its	5-1/2" 17# 1.55 IT&C	~ C-4	
at 4100'. Halliburton cemente	ed w/1000 gals. Superflush 102	+ 800 sv. Halliburton Li	te + 8# solt/sk + 1/4# Floor	g. sei de/d.	
followed by 250 sxs. Premium	Plus w/3#KCL/sk. + .5% Hala	ad 344 + 1/4# Flocele/sk	Displaced w/l.bhl EW 1	cie/sk.	
MSA + 81 bbls. FW w/Lo-Su	orf 300. Plug down at 2:00 pm	12/11/06 Circ 121 sv	omt Programs to the desire	.Z DDIS.	
1500# for 30 minutes no pre-	ssure loss. Released rig at 4:00	n m 12/11/06 DIM	cint. Fiessure lesten casing	g to	
, p	The state of the s	p.m. 12/11/90. DLNI Wa	is nouncu, no representanvo	e present.	
8 Ihereby certify that the foregoing is true an	d correct.	· · · · · · · · · · · · · · · · · · ·			
SIGNED Mary Op Turner	mm n Daillin D				
SIGNED Mary Op Turney	TITLE Drilling D	epartment	DATE <u>December 12</u>	<u>, 1996</u>	
(This space for Federal or State office use)					
·	-				
APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	TITLE		_ DATE		
	ton tester to	Om D	TEC 2 4 199	96	
	see instruction	On Reverse Side	× = 1,190	-	

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States arty false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.