Form 3160-5

| (Formerly 9-331) UNITED STATES DEPARTMENT OF THE INTERIOR RUDEALLOF LAND MANAGEMENT | | | | SUBMIT IN TRIPLICATE (Other Instructions on reverse side) | Budget Bureau No. 1004-0135 Expires August 31, 1985 5.HEASE DESIGNATION AND SERIAL NO. LC-029418-A | | |
|---|--|--|-----------|---|---|--------------------------------------|---------|
| (Do no | t use this form for pro | TICES AND REPOR oposals to drill or to deepen # 51s. CATION FOR PERMIT - 153s. | g sact vo | Minoil Gons Division | TE DUDIE | N, ALLOTTEE OR TRI | BE NAME |
| OIL WELL | GAS WELL | OTHER | | S. 1st Street | ľ | PREEMENT NAME V Unit ^T | |
| 2. NAME OF OPERATOR The Wiser Oil Company | | | | | 8. API WELL NO. 30-015-29273 | | |
| P. O. Box 2568 Hobbs, New Mexico 88241 ACCEPTED | | | | | 9. WELL NO. 217 | | |
| 4. LOCATION OF WELL (Report location clearly and in accordance with any Stat See also space 17 below.) At surface 28' FSL & 1164' FEL Sec. 14-T17S-R31E Unit P | | | | Grayburg Jackson 7-Rivers 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 14-T17S-R31E | | | |
| | 14. PERMIT NO 15. ELEVATIONS (Show whether DF, I 3891' | | | | 12. COUNTY OR PARISH 13. STATE Eddy NM | | |
| 16. | | | te Natur | re of Notice, Report, or Othe | r Data | | |
| NOTICE OF INTENTION TO: | | | | | SEQUENT R | EPORT OF: | |
| TEST WATER SHU | T OFF | PULL OR ALTER CASING | | WATER SHUT-OFF | | REPAIRING WELL | |
| FRACTURE TREAT | | MULTIPLE COMPLETE | | FRACTURE TREATMENT | | ALTERING CASING | |
| SHOOT OR ACIDIZ | E \square | ABANDON* | | SHOOTING OR ACIDIZING | | ABANDONMENT * | |
| REPAIR WELL (Other) | | CHANGE PLANS | | (Other) Spudding, Cemer (Note: Report results of Completion or Recomm | multiple comp | oletion on Well | sing |

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS: (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

MIRU Norton Drilling Co., Rig #5. Spudded 12-1/4" surface hole @ 12:00 a.m., 12/17/96. Drilled hole to 450'. Ran 10 jts. 8-5/8", 20#, ISW-42 ST& C csg. Set at 449'. Halliburton cemented with 325 sx. Class "C" containing 1/4#/sk. Flocele + 2% CaCl. Plug down @ 7:45 p.m.., 12/17/96. Circulated 94 sx. cmt. BLM was notified, no representative present. NU BOP & tested csg. to 1000# for 30 minutes, no pressure loss. WOC 12 hrs.

Drilled 7-7/8" production hole to a depth of 4120'. Ran casing as follows: Ran 99 jts. 5-1/2" 17#, J-55, LT&C csg. Set at 4120'. Halliburton cemented w/1000 gals. Superflush 102 + 850 sx. Halliburton Lite + 8# salt/sk. + 1/4# Flocele/sk. followed by 250 sx. Premium Plus w/3#KCL/sk. + .5% Halad 344 + 1/4# Flocele/sk. Displaced w/l bbl. FW + 12 bbls. MSA + 83 bbls. FW w/Lo-Surf 300. Plug did not hold. Circ. 98 sx. cmt. WOC 1 1/2 hrs. Plug held. Pressure tested casing to 1500# for 30 minutes, no pressure loss. Released rig at 11:00 a.m. 12/22/96. BLM was notified, no representative present

| an to probone. | | | | | | | | |
|--|---------------------------|------------------------|--|--|--|--|--|--|
| 18 Ihereby certify that the foregoing is true and correct. | | | | | | | | |
| SIGNED MALLY SO THERE | TITLE Drilling Department | DATE December 23, 1996 | | | | | | |
| (This space for Federal or State office use) | | | | | | | | |
| APPROVED BY CONDITIONS OF APPROVAL, IF ANY: | TITLE | DATE | | | | | | |

*See Instruction On Reverse Side