

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

NS 1004-0135  
BS13 N 1004-0135

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

dsf

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT --" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well: ☐ OIL WELL ☒ GAS WELL ☐ OTHER

2. Name of Operator  
TEXACO EXPLORATION & PRODUCTION INC.

3. Address and Telephone No. P.O. Box 2100, Denver Colorado 80201 (303)793-4851

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)  
Unit Letter B : 990 Feet From The NORTH Line and 1850 Feet From The  
EAST Line Section 21 Township 17-S Range 31-E

5. Lease Designation and Serial No.  
LC-029420 B

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation  
SKELLY UNIT

8. Well Name and Number  
SKELLY UNIT  
901

9. API Well No.  
30-015-29326

10. Field and Pool, Exploratory Area  
FREN, PADDOCK: UNDESIG. WOLFCAMP: ABO

11. County or Parish, State  
EDDY, NM

12. Check Appropriate Box(s) To Indicate Nature of Notice, Report, or Other Data

TYPE OF SUBMISSION

- ☒ Notice of Intent  
☐ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ OTHER:  
☒ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log Form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Revise intermediate casing setting depth from 3550' to 4800'.

Casing design: 0' - 2200': 8- 5/8", 24#, WC-50, STC  
2200' - 4800': 8- 5/8", 32#, WC-50, LTC

Cement design: 1500 sxs 35/65 POZ Class 'H' W/ 6% gel, 5% salt, 1/4# Flocele (12.4 PPG, 2.14 CF/S, 11.9 GW/S)  
followed by 500 sxs Class 'H' (15.6 PPG, 1.18 CF/S, 5.2 GW/S)

RECEIVED  
1997 AUG -7 A 10:56  
BUREAU OF LAND MGMT.  
ROSWELL OFFICE

14. I hereby certify that the foregoing is true and correct

SIGNATURE C. P. Basham / SETH TITLE Eng. Assistant.  
TYPE OR PRINT NAME Sheilla D. Reed-High

DATE 8/5/97

(This space for Federal or State office use)

APPROVED

CONDITIONS OF APPROVAL, IF ANY:

TITLE

PETROLEUM ENGINEER

DATE

AUG 11 1997

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction