Form 3160-5 (June 1990)

## UN D STATES DEPARTMENT OF THE INTERIOR

(4.1a) (1) (4.1 (3.15)) 0151

**BUREAU OF LAND MANAGEMENT FORM APPROVED** 21282930 Budget Bureau No. 1004-0135 Expires March 31, 1993 5. Lease Designation and Serial No. SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir Use "APPLICATION FOR PERMIT—" for such proposals. LC-029426-B 6. If Indian, Allottee or Tribe Name SUBMIT IN TRIPLICATE 7. If Unit or CA, Agreement Designation 1. Type of Well Gas Well Other Injection Well 8. Well Name and No. 2. Name of Operator **DEVON ENERGY CORPORATION (NEVADA)** H. E. West "B" #94 9. API Well No. 3. Address and Telephone No. 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405) 235-3611 30-015-29349 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage. Sec., T., R., M., or Survey Description) **Grayburg Jackson** 440' FNL & 1980' FEL, Sec. 10-17S-31E 11. County or Parish, State Eddy County, NM

TYPE OF SUBMISSION		TYPE OF AC	TYPE OF ACTION	
Notice of Intent  Subsequent Report  Final Abandonment No	NOV & 0 1397	Abandonment  Recompletion  Plugging Back  Casing Repair  Altering Casing  Other Spud, TD'd & set csg	Change of Plans  New Construction  Non-Routine Fracturing  Water Shut-Off  Conversion to Injection  Dispose Water  (Note: Report results of multiple completion on Well	

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spud well @ 2:00 p.m., 10/29/97.

Ran surface casing as follows: 15 jts 8 5/8" 24# J-55 8rd, set @ 652'.

Cemented casing as follows: Lead – 225 sx 35/65 "C" POZ w/2% CaCl2 + ¼ lb/sk celloflake, wt 12.7 ppg, yield 1.87 cft/sk. Tail – 200 sx "C" w/2% CaCl2, wt 14.8 ppg, yield 1.32 cft/sk. Circ'd cement to surface.

Reached TD of 4150'.

Ran production casing as follows: 93 jts 5 1/2" 15.5# J-55 8rd, set @ 4149', float collar @ 4102'.

Cemented casing as follows: Lead – 1150 sx 35/65 "C" POZ w/5% salt & ¼ lb/sk celloflake, wt 13.05 ppg, yield 1.75 cft/sk. Tail – 275 sx "H" w/10% A10B, 5% salt & ¼ lb/sk celloflake, wt 14.5 ppg, yield 1.57 cft/sk. Circ'd cement to surface.

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to matter within its jurisdiction.

ROSWELL OFFICE

1:01 NON SH b 3: 53

77420