C\5F

Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

all. Oil Cons.		y ; 61
DAY & 1st Street		
Artosia, NM 802	7	ું કા 🕩

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31,1993

ease Designation and Serial No. BUREAU OF LAND MANAGEMENT NM-0467932 SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals 7. If Unit or CA, Agreement Designation JUN 1 0 1897 SUBMIT IN TRIPLICATE I Type of Well Oil Well Well Name and No. W D McIntyre E #3 2. Name of Operator 9. API Well No. Mack Energy Corporation 30-015-29425 3. Address and Telephone No (505)748-1288 10. Field and Pool, or Exploratory Area P.O. Box 960, Artesia, NM 88211-0960 4. Location of Well (Footage, Sec., T. R., M. or Survey Description) Loco Hills Paddock 11. County or Parish, State 2135 FSL 2310 FWL Sec 20 T17S R30E Eddy, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF ACTION TYPE OF SUBMISSION Change of Plans Ahandonment Notice of Intent New Construction Recompletion Non-Routine Fracturing Plugging Back Subsequent Report Water Shut-Off Casing Repair Conversion to Injection Altering Casing Final Abandonment Notice Cement LongString Casing Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work)* 5/24/97 TD 7 7/8" hole @ 4840'. Pump 60 bbl sweep & spot 180 bbls mud. POH & stand back DP. RU Schlumberger & log. 5/25/97 RIH w/113 jts 5 1/2" 17# J-55 LT&C csg. Landed Casing @ 4835'. DV Tool @ 4033' & MK JT @ 3199'. Cemented 1st stage w/175 sx 50/50 C Poz, 2% gel, .5% FL-25, 5# salt. Open DV Tool Circ 53 sx cement. Circ. 6 hrs between stages. Cemented 2nd stage w/485 sx 35/65, 3# salt, 1/4#CF. & 365 sx 50/50 C Poz ,2% gel, .5% FL-25, 5# salt. Circ. 102 sx. 14. I hereby certify that the foregoing is true and correct 6/3/97 Production Clerk Title Signed (This space for Federal or State office use) Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements