Form 3160-5 (November 1983) (Formerly 9-331)

UNITED STATES

SUBMIT IN TRIPLICATE * (Other Instructions on

Budget Bureau No. 1004-0135 Expires August 31, 1985

2	5(
\sim (
C (

DEPART	MENT OF THE INTERIO	reverse side)	Expires August 31, 1985
	LOFIAND MANAGEMENT	, n	5. LEASE DESIGNATION AND SERIAL NO.
SUNDRY NOTICES AND REPORTS ON WELLS		NM-98120	
Do not use this form for a	roposals to drill or to deepen or plug back	JN WELLS	6. IF INDIAN ALLOTTEE OR TRIBE NAME
Use "APPL	ICATION FOR PERMIT - " for such pro	Peaks W F T	hai sives
1.	1		7 UNIT AGREEMENT NAME
OIL GAS WELL WELL	OTHER ST.		Skelly Unit
WELL WELL 2. NAME OF OPERATOR	Water Injection	MAY 1 3 1997	<u></u>
The Wiser Oil Company		MINI I O IOO	8. API WELL NO.
3. ADDRESS OF OPERATOR		WEGO WO WAS TO	30-015-29452
P. O. Box 2568 Hobbs.	Now Movies 99241		9. WELL NO.
4. LOCATION OF WELL (Report locat	tion clearly and in accordance with any sta	CEPTED FOT RECORD	300
See also space 17 below.)	for clearly and in accordance with any se	the requirements:	10. FIELD AND POOL, OR WILDCAT
	SL & 1980' FEL	MAY 4 6 4007	Grayburg Jackson 7-Rivers
Sec. 23- Unit J	T17S-R31E	MAY 1 2 1997	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Cint J		act!	Sec. 23-T17S-R31E
		AV M	300. 23-11/3-R31E
14. PERMIT NO	15. ELEVATIONS (Show whether Di	, RT, OR, etc.)	12. COUNTY OR PARISH 13. STATE
	3869		Eddy NM
16. Check	Appropriate Box to indicate Nat	ure of Notice, Report, or Other	er Data
NOTICE OF IN	FENTION TO:	sun	BSEQUENT REPORT OF:
TEST WATER SHUT OFF	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	
SHOOT OR ACIDIZE			ALTERING CASING
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	, [_]
			ABANDONMENT *
REPAIR WELL	CHANGE PLANS	(Other) Spudding Ceme	nting Surface & Production Casing
	نــا	(Note: Report results of	f multiple completion on Well
(Other)		Completion or Pecom	olation Danast and I am Comm.
 DESCRIBE PROPOSED OR COMPLET proposed work. If well is directionally 	drilled give subsurface locations and man	tinent details, and give pertinent dates	, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)			
MIRI Norton Drilling Co. Rig #7. Smudded 12 1/4" gradene hale (5) 8 45			
MIRU Norton Drilling Co., Rig #7. Spudded 12-1/4" surface hole @ 8:45 p.m., 04/25/97. Drilled hole to 366'. Ran			
8 jts. 8-5/8", 23#, ISW-42 ST& C csg. Set at 364'. Halliburton cemented with 325 sx. Class "C" containing 1/4#/sk.			
Flocele + 2% CaCl. Plug down @ 5:00 a.m., 04/26/97. Circulated 83 sx. cmt. BLM was notified no representative			
present. NU BOP & tested csg. to 1,000# for 30 min., no pressure loss. WOC 12 hrs.			
Drilled 7-7/8" production halo to a double of 4050? Described 2-7/8"			
Drilled 7-7/8" production hole to a depth of 4050'. Ran casing as follows: Ran 99 jts. 5-1/2" 17#, J-55, LT&C csg. Set			
at 4050'. Halliburton cemented w/1000 gals. Superflush 102 + 750 sks. Halliburton Lite + 8# salt/sk. + 1/4# Flocele/sk.			
followed by 250 sks. Premium Plus w/3#KCL/sk. + .5% Halad 344 + 1/4# Flocele/sk. Displaced w/I bbl. FW + 12 bbls.			
MSA + 80 bbls. FW w/Lo-Surf 300. Plug down at 8:45 p.m. 05/01/97. Circulated 11 sxs. cmt. Released rig at 10:45 p.m.			
05/01/97. BLM was notified,	, no representative present. Pr	essure tested csg. to 1500#	for 30 min., no pressure loss
	_	S	probate 1000.
8 Ihereby certify that the foregoing is true an	d correct.		
		m	
SIGNED Mary Jo Turney	TITLE Drilling	<u>Department</u>	DATE <u>May 5, 1997</u>
(This space for Federal or State office use)			
•			
CONDITIONS OF APPROVAL IF ANY	TITLE		DATE