## INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all specific tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

ĺ

## INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

		outheastern I					New Mexico	
T. Anhy	1	Т. (	Canvon	T. Oio	Alamo _	T.	Penn. "B" Penn. "C"	_
T. Salt		424.0 T.	Strawn	📃 T. Kirtla	and-Frui	land T.	Penn. "C"	_
B. Salt		<u> </u>	Atoka	T. Pictu	ured Cliff	is T.	Penn. "D"	_
T Voto	e	848 O T 1	lice	T Cliff	House	т	l eadville	
T. 7 Riv	/ers	1126.0 T. I	Devonian	T. Men	efee	T.	Madison	
T. Quee	en	<u>1740.0</u> T. S	Silurian	T. Poin	t Lookou	ut T.	Elbert	_
T. Grav	bura	2080.0 T.I	Montova	T. <b>M</b> an	COS	I.	McCracken	_
T San	Andrae	2580 0 T (	Simneon	T Gall	in	Т	Ignacio Otzte	
T. Glori	ieta	T. I	McKee	Base C	Greenhor	n <u>T</u> .	Granite	_
T. Pado	lock _	T. I	Ellenburger	<u> </u>	ota	<u>T</u> .		-
T. Glorieta T. McKee T. Paddock T. Ellenburger T. Blinebry T. Gr. Wash			<u>T</u> . <u>Mon</u>	ison	<u>T</u> .	· · · · · · · · · · · · · · · · ·		
1. Ludd I. Delaware Sand			1. 1001	110	۱.			
T. Drinkard T. Bone Springs T. Abo T			T. Entr	ada	<u> </u> .		-	
T. Abo		<u>T</u>		1. vving	gate	<u></u>		-
T. Wolfcamp T T. Penn T				I. Cinir		<u> </u> .		-
I. Penr	<u></u>	<b>[</b> . ,	- <u></u>	1. Perr	nain	!. 		-
I. CISC	O (Bough	C)I.						
			OIL OR GAS	SANDS OF	ZONES	5		
No 1 from to			. No.	3, from		to	••	
No. 2, f	rom	to	******	. No.	4, from		to	••
			IMPORTA					
Include	data or	n rate of water i	inflow and elevation					
No. 1, from to				feet				
No. 3, from to				feet				
		LITHOLO	GY RECORD	Attach add	itional si	neet it necess	ary)	_
From	То	Thickness in Feet	Lithology	From	То	Thickness in Feet		
0.0	150.0	150.0	Red Bed/Sd/Gravel					
150.0	300.0	150.0	Sd & Red Bed	1	1			
300.0			Suareubeu					
422.0	1 1	124.0	Anhy					
	648.0	124.0 226.0	Anhy Salt					
648.0	648.0 1740.0	124.0 226.0 1092.0	Anhy Satt Anhy/Dolo					
648.0 1740.0	648.0 1740.0 2080.0	124.0 226.0 1092.0 340.0	Anhy Sait Anhy/Dolo Anhy/Sd/Dolo					
648.0 1740.0 2080.0	648.0 1740.0 2080.0 2580.0	124.0 226.0 1092.0 340.0 500.0	Anhy Sait Anhy/Dolo Anhy/Sd/Dolo Dolo/Anhy					
648.0 1740.0	648.0 1740.0 2080.0	124.0 226.0 1092.0 340.0	Anhy Sait Anhy/Dolo Anhy/Sd/Dolo					
648.0 1740.0 2080.0	648.0 1740.0 2080.0 2580.0	124.0 226.0 1092.0 340.0 500.0	Anhy Sait Anhy/Dolo Anhy/Sd/Dolo Dolo/Anhy					
648.0 1740.0 2080.0	648.0 1740.0 2080.0 2580.0	124.0 226.0 1092.0 340.0 500.0	Anhy Sait Anhy/Dolo Anhy/Sd/Dolo Dolo/Anhy					
648.0 1740.0 2080.0	648.0 1740.0 2080.0 2580.0	124.0 226.0 1092.0 340.0 500.0	Anhy Sait Anhy/Dolo Anhy/Sd/Dolo Dolo/Anhy					
648.0 1740.0 2080.0	648.0 1740.0 2080.0 2580.0	124.0 226.0 1092.0 340.0 500.0	Anhy Sait Anhy/Dolo Anhy/Sd/Dolo Dolo/Anhy					
648.0 1740.0 2080.0	648.0 1740.0 2080.0 2580.0	124.0 226.0 1092.0 340.0 500.0	Anhy Sait Anhy/Dolo Anhy/Sd/Dolo Dolo/Anhy					
648.0 1740.0 2080.0	648.0 1740.0 2080.0 2580.0	124.0 226.0 1092.0 340.0 500.0	Anhy Sait Anhy/Dolo Anhy/Sd/Dolo Dolo/Anhy					
648.0 1740.0 2080.0	648.0 1740.0 2080.0 2580.0	124.0 226.0 1092.0 340.0 500.0	Anhy Sait Anhy/Dolo Anhy/Sd/Dolo Dolo/Anhy					- ·